CS162
Operating Systems and Systems Programming
Lecture 24

Distributed File Systems

November 23, 2005
Prof. John Kubiatowicz
http://inst.eecs.berkeley.edu/~cs162

Review: Network Communication

- TCP: Reliable byte stream between two processes on different machines over Internet (read, write, flush)
- Socket: an abstraction of a network I/O queue
  - Embodies one side of a communication channel
    - » Same interface regardless of location of other end
    - » Could be local machine (called "UNIX socket") or remote machine (called "network socket")



- Two-phase commit: distributed decision making
  - First, make sure everyone guarantees that they will commit if asked (prepare)
  - Next, ask everyone to commit

Review: Distributed Applications

- Message Abstraction: send/receive messages
  - Already atomic: no receiver gets portion of a message and two receivers cannot get same message
- Interface:
  - Mailbox (`mbox`): temporary holding area for messages
    - » Includes both destination location and queue
  - `Send(message,mbox)`
    - » Send message to remote mailbox identified by `mbox`
  - `Receive(buffer,mbox)`
    - » Wait until `mbox` has message, copy into buffer, and return
    - » If threads sleeping on this mbox, wake up one of them

Review: Byzantine General's Problem



- Byzantine General's Problem (n players):
  - One General
  - n-1 Lieutenants
  - Some number of these (f<n/3) can be insane or malicious
- The commanding general must send an order to his n-1 lieutenants such that:
  - IC1: All loyal lieutenants obey the same order
  - IC2: If the commanding general is loyal, then all loyal lieutenants obey the order he sends

Review: Byzantine General's Problem (con't)

- Impossibility Results:
  - Cannot solve Byzantine General's Problem with n=3 because one malicious player can mess up things



  - With f faults, need n > 3f to solve problem
- Various algorithms exist to solve problem
  - Original algorithm has #messages exponential in n
  - Newer algorithms have message complexity $O(n^2)$
    - » One from MIT, for instance (Castro and Liskov, 1999)
- Use of BFT (Byzantine Fault Tolerance) algorithm
  - Allow multiple machines to make a coordinated decision even if some subset of them (< n/3) are malicious



Review: Remote Procedure Call

- Raw messaging is a bit too low-level for programming
  - Must wrap up information into message at source
  - Must decide what to do with message at destination
  - May need to sit and wait for multiple messages to arrive
- Better option: Remote Procedure Call (RPC)
  - Calls a procedure on a remote machine
  - Client calls:
    `remoteFileSystem→Read("rutabaga");`
  - Translated automatically into call on server:
    `fileSys→Read("rutabaga");`
- Implementation:
  - Request-response message passing (under covers!)
  - "Stub" provides glue on client/server
    - » Client stub is responsible for "marshalling" arguments and "unmarshalling" the return values
    - » Server-side stub is responsible for "unmarshalling" arguments and "marshalling" the return values.
- Marshalling involves (depending on system)
  - Converting values to a canonical form, serializing objects, copying arguments passed by reference, etc.

Goals for Today

- Finish RPC
- Examples of Distributed File Systems
- Cache Coherence Protocols

Note: Some slides and/or pictures in the following are adapted from slides ©2005 Silberschatz, Galvin, and Gagne

RPC Information Flow



RPC Details

- Equivalence with regular procedure call
  - Parameters ⇔ Request Message
  - Result ⇔ Reply message
  - Name of Procedure: Passed in request message
  - Return Address: mbox2 (client return mail box)
- Stub generator: Compiler that generates stubs
  - Input: interface definitions in an "interface definition language (IDL)"
    - » Contains, among other things, types of arguments/return
  - Output: stub code in the appropriate source language
    - » Code for client to pack message, send it off, wait for result, unpack result and return to caller
    - » Code for server to unpack message, call procedure, pack results, send them off
- Cross-platform issues:
  - What if client/server machines are different architectures or in different languages?
    - » Convert everything to/from some canonical form
    - » Tag every item with an indication of how it is encoded (avoids unnecessary conversions).

RPC Details (continued)

- How does client know which mbox to send to?
  - Need to translate name of remote service into network endpoint (Remote machine, port, possibly other info)
  - Binding: the process of converting a user-visible name into a network endpoint
    - » This is another word for "naming" at network level
    - » Static: fixed at compile time
    - » Dynamic: performed at runtime
- Dynamic Binding
  - Most RPC systems use dynamic binding via name service
    - » Name service provides dynmaic translation of service→mbox
  - Why dynamic binding?
    - » Access control: check who is permitted to access service
    - » Fail-over: If server fails, use a different one
- What if there are multiple servers?
  - Could give flexibility at binding time
    - » Choose unloaded server for each new client
  - Could provide same mbox (router level redirect)
    - » Choose unloaded server for each new request
    - » Only works if no state carried from one call to next
- What if multiple clients?
  - Pass pointer to client-specific return mbox in request

Problems with RPC

- Non-Atomic failures
  - Different failure modes in distributed system than on a single machine
  - Consider many different types of failures
    - » User-level bug causes address space to crash
    - » Machine failure, kernel bug causes all processes on same machine to fail
    - » Some machine is compromised by malicious party
  - Before RPC: whole system would crash/die
  - After RPC: One machine crashes/compromised while others keep working
  - Can easily result in inconsistent view of the world
    - » Did my cached data get written back or not?
    - » Did server do what I requested or not?
  - Answer? Distributed transactions/Byzantine Commit
- Performance
  - Cost of Procedure call « same-machine RPC « network RPC
  - Means programmers must be aware that RPC is not free
    - » Caching can help, but may make failure handling complex

Administrivia

- My office hours
  - No office hours Thursday (Thanksgiving)
- Project 4 design document
  - Due Tuesday November 29th
- MIDTERM II: Monday December 5th!
  - 5:30-8:30pm, 10 Evans
  - All material from last midterm and up to previous class
  - Includes virtual memory
- Final Exam
  - December 17th, 12:30 – 3:30, 220 Hearst Gym
- Final Topics: Any suggestions?

Cross-Domain Communication/Location Transparency

- How do address spaces communicate with one another?
  - Shared Memory with Semaphores, monitors, etc…
  - File System
  - Pipes (1-way communication)
  - "Remote" procedure call (2-way communication)
- RPC's can be used to communicate between address spaces on different machines on the same machine
  - Services can be run wherever it's most appropriate
  - Access to local and remote services looks the same
- Examples of modern RPC systems:
  - CORBA (Common Object Request Broker Architecture)
  - DCOM (Distributed COM)
  - RMI (Java Remote Method Invocation)

Microkernel operating systems

- Example: split kernel into application-level servers.
  - File system looks remote, even though on same machine



Monolithic Structure



Microkernel Structure

- Why split the OS into separate domains?
  - Fault isolation: bugs are more isolated (build a firewall)
  - Enforces modularity: allows incremental upgrades of pieces of software (client or server)
  - Location transparent: service can be local or remote
    - » For example in the X windowing system: Each X client can be on a separate machine from X server; Neither has to run on the machine with the frame buffer.

Distributed File Systems



- Distributed File System:
  - Transparent access to files stored on a remote disk
- Naming choices (always an issue):
  - *Hostname*:localname: Name files explicitly
    - » No location or migration transparency
  - *Mounting* of remote file systems
    - » System manager mounts remote file system by giving name and local mount point
    - » Transparent to user: all reads and writes look like local reads and writes to user e.g. /users/sue/foo→/sue/foo on server
  - *A single, global name space:* every file in the world has unique name
    - » Location Transparency: servers can change and files can move without involving user



Virtual File System (VFS)



- VFS: Virtual abstraction similar to local file system
  - Instead of "inodes" has "vnodes"
  - Compatible with a variety of local and remote file systems
    - » provides object-oriented way of implementing file systems
- VFS allows the same system call interface (the API) to be used for different types of file systems
  - The API is to the VFS interface, rather than any specific type of file system

Simple Distributed File System



- Remote Disk: Reads and writes forwarded to server
  - Use RPC to translate file system calls
  - No local caching/can be caching at server-side
- Advantage: Server provides completely consistent view of file system to multiple clients
- Problems? Performance!
  - Going over network is slower than going to local memory
  - Lots of network traffic/not well pipelined
  - Server can be a bottleneck

Use of caching to reduce network load



- Idea: Use caching to reduce network load
  - In practice: use buffer cache at source and destination
- Advantage: if open/read/write/close can be done locally, don't need to do any network traffic…fast!
- Problems:
  - Failure:
    - » Client caches have data not committed at server
  - Cache consistency!
    - » Client caches not consistent with server/each other

Failures



- What if server crashes? Can client wait until server comes back up and continue as before?
  - Any data in server memory but not on disk can be lost
  - Shared state across RPC: What if server crashes after seek? Then, when client does "read", it will fail
  - Message retries: suppose server crashes after it does UNIX "rm foo", but before acknowledgment?
    - » Message system will retry: send it again
    - » How does it know not to delete it again? (could solve with two-phase commit protocol, but NFS takes a more ad hoc approach)
- Stateless protocol: A protocol in which all information required to process a request is passed with request
  - Server keeps no state about client, except as hints to help improve performance (e.g. a cache)
  - Thus, if server crashes and restarted, requests can continue where left off (in many cases)
- What if client crashes?
  - Might lose modified data in client cache

Schematic View of NFS Architecture



Network File System (NFS)

- Three Layers for NFS system
  - UNIX file-system interface: open, read, write, close calls + file descriptors
  - VFS layer: distinguishes local from remote files
    - » Calls the NFS protocol procedures for remote requests
  - NFS service layer: bottom layer of the architecture
    - » Implements the NFS protocol
- NFS Protocol: RPC for file operations on server
  - Reading/searching a directory
  - manipulating links and directories
  - accessing file attributes/reading and writing files
- Write-through caching: Modified data committed to server's disk before results are returned to the client
  - lose some of the advantages of caching
  - time to perform write() can be long
  - Need some mechanism for readers to eventually notice changes! (more on this later)

NFS Continued

- NFS servers are stateless; each request provides all arguments require for execution
  - E.g. reads include information for entire operation, such as `ReadAt(inumber,position)`, not `Read(openfile)`
  - No need to perform network open() or close() on file – each operation stands on its own
- Idempotent: Performing requests multiple times has same effect as performing it exactly once
  - Example: Server crashes between disk I/O and message send, client resend read, server does operation again
  - Example: Read and write file blocks: just re-read or re-write file block – no side effects
  - Example: What about "remove"? NFS does operation twice and second time returns an advisory error
- Failure Model: Transparent to client system
  - Is this a good idea? What if you are in the middle of reading a file and server crashes?
  - Options (NFS Provides both):
    - » Hang until server comes back up (next week?)
    - » Return an error. (Of course, most applications don't know they are talking over network)

NFS Cache consistency

- NFS protocol: weak consistency
  - Client polls server periodically to check for changes
    - » Polls server if data hasn't been checked in last 3-30 seconds (exact timeout it tunable parameter).
    - » Thus, when file is changed on one client, server is notified, but other clients use old version of file until timeout.



  - What if multiple clients write to same file?
    - » In NFS, can get either version (or parts of both)
    - » Completely arbitrary!

Sequential Ordering Constraints

- What sort of cache coherence might we expect?
  - i.e. what if one CPU changes file, and before it's done, another CPU reads file?
- Example: Start with file contents = "A"



- What would we actually want?
  - Assume we want distributed system to behave exactly the same as if all processes are running on single system
    - » If read finishes before write starts, get old copy
    - » If read starts after write finishes, get new copy
    - » Otherwise, get either new or old copy
  - For NFS:
    - » if read starts more than 30 seconds after write, get new copy; otherwise, could get partial update

NFS Pros and Cons

- NFS Pros:
  - Simple, Highly portable
- NFS Cons:
  - Sometimes inconsistent!
  - Doesn't scale to large # clients
    - » Must keep checking to see if caches out of date

Andrew File System

- Andrew File System (AFS, late 80's) → DCE DFS (commercial product)
- Callbacks: Server records who has copy of file
  - On changes, server immediately tells all with old copy
  - No polling bandwidth (continuous checking) needed
- Write through on close
  - Changes not propagated to server until close()
  - Session semantics: updates visible to other clients only after the file is closed
    - » As a result, do not get partial writes: all or nothing!
    - » Although, for processes on local machine, updates visible immediately to other programs who have file open
- In AFS, everyone who has file open sees old version
  - Don't get newer versions until reopen file

Andrew File System (con't)

- Data cached on local disk of client as well as memory
  - On open with a cache miss (file not on local disk):
    - » Get file from server, set up callback with server
  - On write followed by close:
    - » Send copy to server; tells all clients with copies to fetch new version from server on next open (using callbacks)
- What if server crashes? Lose all callback state!
  - Reconstruct callback information from client: go ask everyone "who has which files cached?"
- AFS Pro: Relative to NFS, less server load:
  - Disk as cache ⇒ more files can be cached locally
  - Callbacks ⇒ server not involved if file is read-only
- For both AFS and NFS: central server is bottleneck!
  - Performance: all writes→server, cache misses→server
  - Availability: Server is single point of failure
  - Cost: server machine's high cost relative to workstation

Conclusion

- Remote Procedure Call (RPC): Call procedure on remote machine
  - Provides same interface as procedure
  - Automatic packing and unpacking of arguments without user programming (in stub)
- VFS: Virtual File System layer
  - Provides mechanism which gives same system call interface for different types of file systems
- Distributed File System:
  - Transparent access to files stored on a remote disk
    - » NFS: Network File System
    - » AFS: Andrew File System
  - Caching for performance
- Cache Consistency: Keeping contents of client caches consistent with one another
  - If multiple clients, some reading and some writing, how do stale cached copies get updated?
  - NFS: check periodically for changes
  - AFS: clients register callbacks so can be notified by server of changes