

## 1 Creating Cats

Given the `Animal` class, fill in the definition of the `Cat` class so that it makes a "Meow!" noise when `greet()` is called. Assume this noise is all caps for kittens (less than 2 years old).

```
1 public class Animal {
2     protected String name, noise;
3     protected int age;
4     public Animal(String name, int
5         age) {
6         this.name = name;
7         this.age = age;
8         this.noise = "Huh?";
9     }
10    public String makeNoise() {
11        if (age < 2) {
12            return
13                noise.toUpperCase();
14        }
15        return noise;
16    }
17    public String greet() {
18        return name + ": " +
19            makeNoise();
20    }
21 }
```

```
class Cat extends Animal {
    public Cat(String name, int
        age) {
        super(name, age);
        this.noise = "Meow!";
    }
}
```

Inheritance is powerful because it allows us to reuse code for related classes. With the `Cat` class here, we just have to re-write the constructor to get all the goodness of the `Animal` class.

Why is it necessary to call `super(name, age);` within the `Cat` constructor? It turns out that a subclass' constructor by default always calls the superclass constructor. If we didn't specify the call to the `Animal` superclass constructor that takes in a `String` and a `int`, we'd get a compiler error. This is because the default superclass constructor (`super();`) would have been called. Only problem is that the `Animal` class has no such zero-argument constructor!

By explicitly calling `super(name, age);` in the first line of the `Cat` constructor, we avoid calling the default superclass constructor.

Similarly, not providing any explicit constructor at all in the `Cat` implementation would also result in code that does not compile. This is because when there are no constructors available in a class, Java automatically inserts a no-argument constructor for you. In that no-argument constructor, Java will then attempt to call the default superclass constructor, which again, does not exist.

Also note that declaring a `noise` field at the top of the `Cat` class would not be correct. Since in Java, fields are bound at compile time, when the superclass's `makeNoise()` function calls upon `noise`, we will receive "Huh?". Because of this confusing subtlety of Java, which is called field hiding, it is generally a bad idea to have an instance variable in both a superclass and a subclass with the same name.

## 2 Impala-ments

---

a) We have two interfaces, `BigBaller` and `ShotCaller`. We also have `LilTroy`, a concrete class, which should implement `BigBaller` and `ShotCaller`. Fill out the blank lines below so that the code compiles correctly.

```
1 interface BigBaller {
2     void ball();
3 }
4 interface ShotCaller {
5     void callShots();
6 }
7 public class LilTroy implements BigBaller, ShotCaller {
8     public void ball() {
9         System.out.println("Wanna be a, baller");
10    }
11    public void callShots() {
12        System.out.println("Shot caller");
13    }
14    public void rap() {
15        System.out.println("Say: Twenty inch blades on the Impala");
16    }
17 }
```

b) We have a `BallCourt` where ballers should be able to come and play. However, the below code demonstrates an example of bad program design. Right now, only `LilTroy` instances can ball.

```
1 public class BallCourt {
2     public void play(LilTroy lilTroy) {
3         lilTroy.ball();
4     }
5 }
```

Fix the `play` method so that all the `BigBallers` can ball.

```
public class BallCourt {
    public void play(BigBaller baller) {
        baller.ball();
    }
}
```

c) We discover that Rappers have some common behaviors, leading to the following class.

```
1 class Rapper {
2     public abstract String getLine();
3     public final void rap() {
4         System.out.println("Say: " + getLine());
5     }
6 }
```

Will the above class compile? If not, why not? How can we fix it? **This class will NOT compile.** `Rapper` class has a method names `getLine`, which is declared `abstract`. It does not have any method implementation. Would it be possible to create an object from a class where a method lacks the implementation? Definitely not! By adding the `abstract` keyword before the `class`

keyword, the class will compile normally. The first line should look like `abstract class Rapper`.

d) Rewrite `LilTroy` so that `LilTroy` extends `Rapper` and displays exactly the same behavior as in part a) *without* overriding the `rap` method (in fact, you *cannot* override final methods).

```
public class LilTroy extends Rapper implements BigBaller, ShotCaller {
```

```
    @Override
    public void ball() {
        System.out.println("Wanna be a, baller");
    }

    @Override
    public void callShots() {
        System.out.println("Shot caller");
    }

    @Override
    public String getLine() {
        return "Twenty inch blades on the Impala";
    }
}
```

Note that most of the `Rapper`'s implementation can be reused in all its subclasses, as long as they correctly implement `getLine`. `Rapper` captures a reusable and common behavior (`rap`), while delegating some parts of implementations to its subclasses.

Here, we also wrote `@Override` above the methods we intended to override. While this annotation line is optional, if included, the compiler will bring any such labeled functions that aren't actually correctly overriding anything to your attention.

### 3 Raining Cats & Dogs

We now have the `Dog` class! (Assume that the `Cat` and `Dog` classes are both in the same file as the `Animal` class.)

```
1 class Dog extends Animal {
2     public Dog(String name, int age) {
3         super(name, age);
4         noise = "Woof!";
5     }
6     public void playFetch() {
7         System.out.println("Fetch, " + name + "!");
8     }
9 }
```

Consider the following main function in the `Animal` class. Decide whether each line causes a compile time error, a runtime error, or no error. If a line works correctly, draw a box-and-pointer diagram and/or note what the line prints.

```
public static void main(String[] args) {

    Cat nyan = new Animal("Nyan Cat", 5);    (A) compile time error
```

The static type of `nyan` must be the same class or a superclass of the dynamic type. It doesn't make sense for the dynamic type to be the superclass of the static type.

```
Animal a = new Cat("Olivia Benson", 3); (B) no error
a = new Dog("Fido", 7); (C) no error
System.out.println(a.greet()); (D) "Fido: Woof!"
a.playFetch(); (E) compile time error
```

The compiler attempts to find the method `playFetch` in the `Animal` class (`a`'s static type). Because it does not find it there, there is an error because the compiler does not check the `Dog` class (dynamic type) at compile time.

```
Dog d1 = a; (F) compile time error
```

The compiler views the type of variable `a` to be `Animal` because that is its static type. It doesn't make sense to assign an `Animal` to a `Dog` variable.

```
Dog d2 = (Dog) a; (G) no error
```

The `(Dog) a` part is a cast. Casting tells the compiler to treat `a` as if it were a `Dog`. Casting changes the compiler's perception of a variable's dynamic type for the one line of the cast. After that line, `a`'s static type goes back to being `Animal`.

```
d2.playFetch(); (H) "Fetch, Fido!"
(Dog) a.playFetch(); (I) compile time error
```

Parentheses are important when casting. Here, the cast happens after `a.playFetch()` is evaluated. The return type of `playFetch()` is `void`, and it makes no sense to cast something `void` to a `Dog`. This is simply invalid. Something that would work is: `((Dog) a).playFetch();`

```
Animal imposter = new Cat("Pedro", 12); (J) no error
Dog fakeDog = (Dog) imposter; (K) runtime error
```

The compiler sees that we'd like to treat `imposter` like a `Dog`. `imposter`'s static type is `Animal`, so it's possible that its dynamic type is actually `Dog`. However, at runtime, when the cast actually happens, we see a `ClassCastException` because the dynamic type of `imposter` (`Cat`) is not compatible with `Dog`.

```
Cat failImposter = new Cat("Jimmy", 21); (L) no error
Dog failDog = (Dog) failImposter; (M) compile time error
```

The compiler sees that we'd like to treat `failImposter` like a `Dog`. However, unlike the example above, `failImposter`'s static type is `Cat`, so it's impossible that its dynamic type is actually `Dog`. Thus, the compiler states that these are inconvertible (incompatible) types.

```
}
```

## 4 Bonus: An Exercise in Inheritance Misery

Cross out any lines that cause compile or runtime errors. What does the main program output after removing those lines?

Moral of the story: fields are hidden if also defined in the subclass, and therefore you should avoid doing that because it makes the code confusing.

```
class A {
    int x = 5;
    public void m1() {System.out.println("Am1-> " + x);}
    public void m2() {System.out.println("Am2-> " + this.x);}
    public void update() {x = 99;}
} class B extends A {
    int x = 10;
    public void m2() {System.out.println("Bm2-> " + x);}
    public void m3() {System.out.println("Bm3-> " + super.x);}
    public void m4() {System.out.print("Bm4-> "); super.m2();}
} class C extends B {
    int y = x + 1;
    public void m2() {System.out.println("Cm2-> " + super.x);}
    /* public void m3() {System.out.println("Cm3-> " + super.super.x);} */
```

[super.super is invalid syntax.](#)

```
public void m4() {System.out.println("Cm4-> " + y);}
/* public void m5() {System.out.println("Cm5-> " + super.y);} */
```

[C's superclass B, and B's superclass A both don't have the variable y.](#)

```
} class D {
    public static void main (String[] args) {
        A b0 = new B();
        System.out.println(b0.x);      (A) 5
        b0.m1();                       (B) Am1->5
        b0.m2();                       (C) Bm2->10
        /* b0.m3(); */                 (D) compile time error; no m3() in A.

        B b1 = new B();
        b1.m3();                       (E) Bm3->5
        b1.m4();                       (F) Bm4->Am2->5

        A c0 = new C();
        c0.m1();                       (G) Am1->5

        A a1 = (A) c0;
        C c2 = (C) a1;
        c2.m4();                       (H) Cm4->11
        ((C) c0).m3();                 (I) Bm3->5

        b0.update();
        b0.m1();                       (J) Am1->99
    }}
```

[If you're curious, you can read more about field hiding at this link.](#)