**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

**/B:** 3.5" floppy drive
To use with PCs or Macs, use a DOS-formatted disk.
Note that all filenames are converted to upper case on the DOS disk.

Sample commands:

```
doscp hello.txt /B:/hello.txt     (copies "hello.txt" from UNIX disk to floppy)
doscp /B:/hello.txt hello.txt     (copies "hello.txt" from floppy to UNIX disk)
dosls /B:                         (lists all the files on the floppy)
```

Please see */usr/pub/HP.floppy.drives* for more information.

## 8mm tape drive on geri.EECS:

| | |
|---|---|
| **/dev/8mm.norewind** | (rewinds automatically) |
| **/dev/8mm.rewind** | (does not rewind automatically) |

Uses standard 8mm video or data tapes.
Read and write files with standard UNIX 'tar' commands (type *man tar* for details).

Sample UNIX commands:

```
setenv TAPE /dev/8mm.norewind     (assigns default drive name)
tar tf $TAPE                      (lists files on the tape)
tar cf $TAPE my_directory         (writes contents of my_directory onto tape)
tar xf $TAPE new_directory        (copies contents of next tape file into new_directory)
mt -t $TAPE offl                  (rewinds and ejects tape)
```

Please see */usr/pub/tape.drives* for more information.