CS162
Operating Systems and Systems Programming
Lecture 20

Reliability and Access Control / Distributed Systems

November 7, 2007

Prof. John Kubiatowicz
http://inst.eecs.berkeley.edu/~cs162

Review: Example of Multilevel Indexed Files

- Multilevel Indexed Files: (from UNIX 4.1 BSD)
  - Key idea: efficient for small files, but still allow big files
  - File Header format:
    - » First 10 ptrs to data blocks
    - » Block 11 points to "indirect block" containing 256 blocks
    - » Block 12 points to "doubly-indirect block" containing 256 indirect blocks for total of 64K blocks
    - » Block 13 points to a triply indirect block (16M blocks)



- UNIX 4.1 Pros and cons
  - Pros: Simple (more or less)
    Files can easily expand (up to a point)
    Small files particularly cheap and easy
  - Cons: Lots of seeks
    Very large files must read many indirect block (four I/Os per block!)

Review: UNIX BSD 4.2

- Inode Structure Same as BSD 4.1 (same file header and triply indirect blocks), except incorporated ideas from DEMOS:
  - Uses bitmap allocation in place of freelist
  - Attempt to allocate files contiguously
  - 10% reserved disk space
  - Skip-sector positioning
- BSD 4.2 Fast File System (FFS)
  - File Allocation and placement policies
    - » Put each new file at front of different range of blocks
    - » To expand a file, you first try successive blocks in bitmap, then choose new range of blocks
  - Inode for file stored in same "cylinder group" as parent directory of the file
  - Store files from same directory near each other
- Note: I put up the original FFS paper as reading for last lecture (and on Handouts page).

Goals for Today

- File Caching
- Durability
- Authorization
- Distributed Systems

Note: Some slides and/or pictures in the following are adapted from slides ©2005 Silberschatz, Galvin, and Gagne. Many slides generated from my lecture notes by Kubiatowicz.

Where are inodes stored?

- In early UNIX and DOS/Windows' FAT file system, headers stored in special array in outermost cylinders
  - Header not stored near the data blocks. To read a small file, seek to get header, seek back to data.
  - Fixed size, set when disk is formatted. At formatting time, a fixed number of inodes were created (They were each given a unique number, called an "inumber")

Where are inodes stored?

- Later versions of UNIX moved the header information to be closer to the data blocks
  - Often, inode for file stored in same "cylinder group" as parent directory of the file (makes an ls of that directory run fast).
  - Pros:
    - » UNIX BSD 4.2 puts a portion of the file header array on each cylinder. For small directories, can fit all data, file headers, etc in same cylinder⇒no seeks!
    - » File headers much smaller than whole block (a few hundred bytes), so multiple headers fetched from disk at same time
    - » Reliability: whatever happens to the disk, you can find many of the files (even if directories disconnected)
  - Part of the Fast File System (FFS)
    - » General optimization to avoid seeks

In-Memory File System Structures



- Open system call:
  - Resolves file name, finds file control block (inode)
  - Makes entries in per-process and system-wide tables
  - Returns index (called "file handle") in open-file table



- Read/write system calls:
  - Use file handle to locate inode
  - Perform appropriate reads or writes

File System Caching

- Key Idea: Exploit locality by caching data in memory
  - Name translations: Mapping from paths→inodes
  - Disk blocks: Mapping from block address→disk content
- **Buffer Cache:** Memory used to cache kernel resources, including disk blocks and name translations
  - Can contain "dirty" blocks (blocks yet on disk)
- Replacement policy? LRU
  - Can afford overhead of timestamps for each disk block
  - Advantages:
    - » Works very well for name translation
    - » Works well in general as long as memory is big enough to accommodate a host's working set of files.
  - Disadvantages:
    - » Fails when some application scans through file system, thereby flushing the cache with data used only once
    - » Example: `find . -exec grep foo {} \;`
- Other Replacement Policies?
  - Some systems allow applications to request other policies
  - Example, 'Use Once':
    - » File system can discard blocks as soon as they are used

File System Caching (con't)

- Cache Size: How much memory should the OS allocate to the buffer cache vs virtual memory?
  - Too much memory to the file system cache ⇒ won't be able to run many applications at once
  - Too little memory to file system cache ⇒ many applications may run slowly (disk caching not effective)
  - Solution: adjust boundary dynamically so that the disk access rates for paging and file access are balanced
- Read Ahead Prefetching: fetch sequential blocks early
  - Key Idea: exploit fact that most common file access is sequential by prefetching subsequent disk blocks ahead of current read request (if they are not already in memory)
  - Elevator algorithm can efficiently interleave groups of prefetches from concurrent applications
  - How much to prefetch?
    - » Too many imposes delays on requests by other applications
    - » Too few causes many seeks (and rotational delays) among concurrent file requests

File System Caching (con't)

- Delayed Writes: Writes to files not immediately sent out to disk
  - Instead, `write()` copies data from user space buffer to kernel buffer (in cache)
    - » Enabled by presence of buffer cache: can leave written file blocks in cache for a while
    - » If some other application tries to read data before written to disk, file system will read from cache
  - Flushed to disk periodically (e.g. in UNIX, every 30 sec)
  - Advantages:
    - » Disk scheduler can efficiently order lots of requests
    - » Disk allocation algorithm can be run with correct size value for a file
    - » Some files need never get written to disk! (e..g temporary scratch files written /tmp often don't exist for 30 sec)
  - Disadvantages
    - » What if system crashes before file has been written out?
    - » Worse yet, what if system crashes before a directory file has been written out? (lose pointer to inode!)

Important "ilities"

- Availability: the probability that the system can accept and process requests
  - Often measured in "nines" of probability. So, a 99.9% probability is considered "3-nines of availability"
  - Key idea here is independence of failures
- Durability: the ability of a system to recover data despite faults
  - This idea is fault tolerance applied to data
  - Doesn't necessarily imply availability: information on pyramids was very durable, but could not be accessed until discovery of Rosetta Stone
- Reliability: the ability of a system or component to perform its required functions under stated conditions for a specified period of time (IEEE definition)
  - Usually stronger than simply availability: means that the system is not only "up", but also working correctly
  - Includes availability, security, fault tolerance/durability
  - Must make sure data survives system crashes, disk crashes, other problems

How to make file system durable?

- Disk blocks contain Reed-Solomon error correcting codes (ECC) to deal with small defects in disk drive
  - Can allow recovery of data from small media defects
- Make sure writes survive in short term
  - Either abandon delayed writes or
  - use special, battery-backed RAM (called non-volatile RAM or NVRAM) for dirty blocks in buffer cache.
- Make sure that data survives in long term
  - Need to replicate! More than one copy of data!
  - Important element: independence of failure
    - » Could put copies on one disk, but if disk head fails…
    - » Could put copies on different disks, but if server fails…
    - » Could put copies on different servers, but if building is struck by lightning….
    - » Could put copies on servers in different continents…
- RAID: Redundant Arrays of Inexpensive Disks
  - Data stored on multiple disks (redundancy)
  - Either in software or hardware
    - » In hardware case, done by disk controller; file system may not even know that there is more than one disk in use

Administrivia

- MIDTERM II: Monday December 4th
  - 4:00—7:00pm, 10 Evans
  - All material from last midterm and up to previous Wednesday (11/29)
  - Includes virtual memory
- Final Exam
  - December 17th, 5:00pm-8:00pm

RAID 1: Disk Mirroring/Shadowing



- Each disk is fully duplicated onto its "shadow"
  - For high I/O rate, high availability environments
  - Most expensive solution: 100% capacity overhead
- Bandwidth sacrificed on write:
  - Logical write = two physical writes
  - Highest bandwidth when disk heads and rotation fully synchronized (hard to do exactly)
- Reads may be optimized
  - Can have two independent reads to same data
- Recovery:
  - Disk failure ⇒ replace disk and copy data to new disk
  - Hot Spare: idle disk already attached to system to be used for immediate replacement

RAID 5+: High I/O Rate Parity

- Data stripped across multiple disks
  - Successive blocks stored on successive (non-parity) disks
  - Increased bandwidth over single disk
- Parity block (in green) constructed by XORing data bocks in stripe
  - P0=D0⊕D1⊕D2⊕D3
  - Can destroy any one disk and still reconstruct data
  - Suppose D3 fails, then can reconstruct: D3=D0⊕D1⊕D2⊕P0



- Later in term: talk about spreading information widely across internet for durability.

Hardware RAID: Subsystem Organization



- Some systems duplicate *all* hardware, namely controllers, busses, etc.

Log Structured and Journaled File Systems

- Better reliability through use of log
  - All changes are treated as *transactions*.
    - » A transaction either happens *completely* or *not at all*
  - A transaction is *committed* once it is written to the log
    - » Data forced to disk for reliability
    - » Process can be accelerated with NVRAM
  - Although File system may not be updated immediately, data preserved in the log
- Difference between "Log Structured" and "Journaled"
  - Log Structured Filesystem (LFS): data stays in log form
  - Journaled Filesystem: Log used for recovery
- For Journaled system:
  - Log used to asynchronously update filesystem
    - » Log entries removed after used
  - After crash:
    - » Remaining transactions in the log performed ("Redo")
- Examples of Journaled File Systems:
  - Ext3 (Linux), XFS (Unix), etc.

Remote File Systems: Virtual File System (VFS)



- VFS: Virtual abstraction similar to local file system
  - Instead of "inodes" has "vnodes"
  - Compatible with a variety of local and remote file systems
    - » provides object-oriented way of implementing file systems
- VFS allows the same system call interface (the API) to be used for different types of file systems
  - The API is to the VFS interface, rather than any specific type of file system

Network File System (NFS)

- Three Layers for NFS system
  - UNIX file-system interface: open, read, write, close calls + file descriptors
  - VFS layer: distinguishes local from remote files
    - » Calls the NFS protocol procedures for remote requests
  - NFS service layer: bottom layer of the architecture
    - » Implements the NFS protocol
- NFS Protocol: remote procedure calls (RPC) for file operations on server
  - Reading/searching a directory
  - manipulating links and directories
  - accessing file attributes/reading and writing files
- NFS servers are stateless; each request provides all arguments require for execution
- Modified data must be committed to the server's disk before results are returned to the client
  - lose some of the advantages of caching
  - Can lead to weird results: write file on one client, read on other, get old data

Schematic View of NFS Architecture



Authorization: Who Can Do What?

- How do we decide who is authorized to do actions in the system?
- Access Control Matrix: contains all permissions in the system
  - Resources across top
    - » Files, Devices, etc…
  - Domains in columns
    - » A domain might be a user or a group of permissions
    - » E.g. above: User D3 can read F2 or execute F3
  - In practice, table would be huge and sparse!

domain \ object	F_1	F_2	F_3	printer
D_1	read		read	
D_2				print
D_3		read	execute	
D_4	read write		read write	

Authorization: Two Implementation Choices

- Access Control Lists: store permissions with object
  - Still might be lots of users!
  - UNIX limits each file to: r,w,x for owner, group, world
  - More recent systems allow definition of groups of users and permissions for each group
  - ACLs allow easy changing of an object's permissions
    - » Example: add Users C, D, and F with rw permissions
- Capability List: each process tracks which objects has permission to touch
  - Popular in the past, idea out of favor today
  - Consider page table: Each process has list of pages it has access to, not each page has list of processes …
  - Capability lists allow easy changing of a domain's permissions
    - » Example: you are promoted to system administrator and should be given access to all system files

Authorization: Combination Approach

- Users have capabilities, called "groups" or "roles"
  - Everyone with particular group access is "equivalent" when accessing group resource
  - Like passport (which gives access to country of origin)
- Objects have ACLs
  - ACLs can refer to users or groups
  - Change object permissions object by modifying ACL
  - Change broad user permissions via changes in group membership
  - Possessors of proper credentials get access

Authorization: How to Revoke?

- How does one revoke someone's access rights to a particular object?
  - Easy with ACLs: just remove entry from the list
  - Takes effect immediately since the ACL is checked on each object access
- Harder to do with capabilities since they aren't stored with the object being controlled:
  - Not so bad in a single machine: could keep all capability lists in a well-known place (e.g., the OS capability table).
  - Very hard in distributed system, where remote hosts may have crashed or may not cooperate (more in a future lecture)

Revoking Capabilities

- Various approaches to revoking capabilities:
  - Put expiration dates on capabilities and force reacquisition
  - Put epoch numbers on capabilities and revoke all capabilities by bumping the epoch number (which gets checked on each access attempt)
  - Maintain back pointers to all capabilities that have been handed out (Tough if capabilities can be copied)
  - Maintain a revocation list that gets checked on every access attempt

Centralized vs Distributed Systems



Client/Server Model

Peer-to-Peer Model

- Centralized System: System in which major functions are performed by a single physical computer
  - Originally, everything on single computer
  - Later: client/server model
- Distributed System: physically separate computers working together on some task
  - Early model: multiple servers working together
    - » Probably in the same room or building
    - » Often called a "cluster"
  - Later models: peer-to-peer/wide-spread collaboration

Distributed Systems: Motivation/Issues

- Why do we want distributed systems?
  - Cheaper and easier to build lots of simple computers
  - Easier to add power incrementally
  - Users can have complete control over some components
  - Collaboration: Much easier for users to collaborate through network resources (such as network file systems)
- The *promise* of distributed systems:
  - Higher availability: one machine goes down, use another
  - Better durability: store data in multiple locations
  - More security: each piece easier to make secure
- Reality has been disappointing
  - Worse availability: depend on every machine being up
    - » Lamport: "a distributed system is one where I can't do work because some machine I've never heard of isn't working!"
  - Worse reliability: can lose data if any machine crashes
  - Worse security: anyone in world can break into system
- Coordination is more difficult
  - Must coordinate multiple copies of shared state information (using only a network)
  - What would be easy in a centralized system becomes a lot more difficult

Distributed Systems: Goals/Requirements

- Transparency: the ability of the system to mask its complexity behind a simple interface
- Possible transparencies:
  - Location: Can't tell where resources are located
  - Migration: Resources may move without the user knowing
  - Replication: Can't tell how many copies of resource exist
  - Concurrency: Can't tell how many users there are
  - Parallelism: System may speed up large jobs by spliting them into smaller pieces
  - Fault Tolerance: System may hide varoius things that go wrong in the system
- Transparency and collaboration require some way for different processors to communicate with one another



Networking Definitions



- **Network:** physical connection that allows two computers to communicate
- **Packet:** unit of transfer, sequence of bits carried over the network
  - Network carries packets from one CPU to another
  - Destination gets interrupt when packet arrives
- **Protocol:** agreement between two parties as to how information is to be transmitted

Broadcast Networks

- **Broadcast Network:** Shared Communication Medium



  - Shared Medium can be a set of wires
    - » Inside a computer, this is called a bus
    - » All devices simultaneously connected to devices



  - Originally, Ethernet was a broadcast network
    - » All computers on local subnet connected to one another
  - More examples (wireless: medium is air): cellular phones, GSM GPRS, EDGE, CDMA 1xRTT, and 1EvDO

Broadcast Networks Details



- **Delivery:** When you broadcast a packet, how does a receiver know who it is for? (packet goes to everyone!)
  - Put header on front of packet: [Destination | Packet]
  - Everyone gets packet, discards if not the target
  - In Ethernet, this check is done in hardware
    - » No OS interrupt if not for particular destination
  - This is layering: we're going to build complex network protocols by layering on top of the packet

Broadcast Network Arbitration

- **Arbitration:** Act of negotiating use of shared medium
  - What if two senders try to broadcast at same time?
  - Concurrent activity but can't use shared memory to coordinate!
- Aloha network (70's): packet radio within Hawaii
  - Blind broadcast, with checksum at end of packet. If received correctly (not garbled), send back an acknowledgement. If not received correctly, discard.
    - » Need checksum anyway – in case airplane flies overhead
  - Sender waits for a while, and if doesn't get an acknowledgement, re-transmits.
  - If two senders try to send at same time, both get garbled, both simply re-send later.
  - Problem: Stability: what if load increases?
    - » More collisions ⇒ less gets through ⇒more resent ⇒ more load… ⇒ More collisions…
    - » Unfortunately: some sender may have started in clear, get scrambled without finishing



Carrier Sense, Multiple Access/Collision Detection

- Ethernet (early 80's): first practical local area network
  - It is the most common LAN for UNIX, PC, and Mac
  - Use wire instead of radio, but still broadcast medium
- Key advance was in arbitration called CSMA/CD: Carrier sense, multiple access/collision detection
  - Carrier Sense: don't send unless idle
    - » Don't mess up communications already in process
  - Collision Detect: sender checks if packet trampled.
    - » If so, abort, wait, and retry.
  - Backoff Scheme: Choose wait time before trying again
- How long to wait after trying to send and failing?
  - What if everyone waits the same length of time? Then, they all collide again at some time!
  - Must find way to break up shared behavior with nothing more than shared communication channel
- Adaptive randomized waiting strategy:
  - Adaptive and Random: First time, pick random wait time with some initial mean. If collide again, pick random value from bigger mean wait time. Etc.
  - Randomness is important to decouple colliding senders
  - Scheme figures out how many people are trying to send!

Point-to-point networks



- Why have a shared bus at all? Why not simplify and only have point-to-point links + routers/switches?
  - Didn't used to be cost-effective
  - Now, easy to make high-speed switches and routers that can forward packets from a sender to a receiver.
- Point-to-point network: a network in which every physical wire is connected to only two computers
- Switch: a bridge that transforms a shared-bus configuration into a point-to-point network.
- Router: a device that acts as a junction between two networks to transfer data packets among them.

Point-to-Point Networks Discussion

- Advantages:
  - Higher link performance
    - » Can drive point-to-point link faster than broadcast link since less capacitance/less echoes (from impedance mismatches)
  - Greater aggregate bandwidth than broadcast link
    - » Can have multiple senders at once
  - Can add capacity incrementally
    - » Add more links/switches to get more capacity
  - Better fault tolerance (as in the Internet)
  - Lower Latency
    - » No arbitration to send, although need buffer in the switch
- Disadvantages:
  - More expensive than having everyone share broadcast link
  - However, technology costs now much cheaper
- Examples
  - ATM (asynchronous transfer mode)
    - » The first commercial point-to-point LAN
    - » Inspiration taken from telephone network
  - Switched Ethernet
    - » Same packet format and signaling as broadcast Ethernet, but only two machines on each ethernet.

Point-to-Point Network design



- Switches look like computers: inputs, memory, outputs
  - In fact probably contains a processor
- Function of switch is to forward packet to output that gets it closer to destination
- Can build big crossbar by combining smaller switches



Flow control options



- What if everyone sends to the same output?
  - Congestion—packets don't flow at full rate
- In general, what if buffers fill up?
  - Need flow control policy
- Option 1: no flow control. Packets get dropped if they arrive and there's no space
  - If someone sends a lot, they are given buffers and packets from other senders are dropped
  - Internet actually works this way
- Option 2: Flow control between switches
  - When buffer fills, stop inflow of packets
  - Problem: what if path from source to destination is completely unused, but goes through some switch that has buffers filled up with unrelated traffic?

Flow Control (con't)

- Option 3: Per-flow flow control.
  - Allocate a separate set of buffers to each end-to-end stream and use separate "don't send me more" control on each end-to-end stream



- Problem: fairness
  - Throughput of each stream is entirely dependent on topology, and relationship to bottleneck
- Automobile Analogy
  - At traffic jam, one strategy is merge closest to the bottleneck
    - » Why people get off at one exit, drive 500 feet, merge back into flow
    - » Ends up slowing everybody else a huge amount
  - Also why have control lights at on-ramps
    - » Try to keep from injecting more cars than capacity of road (and thus avoid congestion)

Conclusion

- Important system properties
  - Availability: how often is the resource available?
  - Durability: how well is data preserved against faults?
  - Reliability: how often is resource performing correctly?
- Use of Log to improve Reliability
  - Journaled file systems such as ext3
- RAID: Redundant Arrays of Inexpensive Disks
  - RAID1: mirroring, RAID5: Parity block
- Authorization
  - Controlling access to resources using
    - » Access Control Lists
    - » Capabilities
- Network: physical connection that allows two computers to communicate
  - Packet: unit of transfer, sequence of bits carried over the network