

Q1. Perceptron and Kernels

A kernel is a mapping $K(x, y)$ from pairs vectors in \mathbb{R}^d into the real numbers such that $K(x, y) = \Phi(x) \cdot \Phi(y)$ where Φ is a mapping from \mathbb{R}^d into \mathbb{R}^D where D is possibly different from d and even infinite. We say that a mapping $K(x, y)$ for which such Φ exists is a valid kernel.

(a) The following binary class data has two features, A and B .

Index	A	B	Class
1.	1	1	1
2.	0	3	-1
3.	1	-1	1
4.	3	0	-1
5.	-1	1	1
6.	0	-3	-1
7.	-1	-1	1
8.	-3	0	-1

(i) Select all true statements:

- This data is linearly separable.
- This data is linearly separable if we use a feature map $\phi((A, B)) = (A^2, B^2, 1)$.
- There exists a kernel such that this data is linearly separable.
- For all datasets in which no data point is labeled in more than one distinct way, there exists a kernel such that the data is linearly separable.
- For all datasets, there exists a kernel such that the data is linearly separable.
- For all valid kernels, there exists a dataset with at least one point from each class that is linearly separable under that kernel.
- None of the above.

We will be running both the primal (normal) binary (not multiclass) perceptron and dual binary perceptron algorithms on this dataset. We will initialize the weight vector w to $(1, 1)$ for the primal perceptron algorithm. Accordingly, we will initialize the α vector to $(1, 0, 0, 0, 0, 0, 0, 0)$ for the dual perceptron algorithm with the kernel $K(x, y) = x \cdot y$. Pass through the data using the indexing order provided. There is no bias term.

Write your answer in the box provided. Show your work outside of the boxes to have a chance at receiving partial credit.

(ii) What is the first misclassified point?

(iii) For the *primal* perceptron algorithm, what is the weight vector after the first weight update?

For your convenience, the data is duplicated on this page.

Index	A	B	Class
1.	1	1	1
2.	0	3	-1
3.	1	-1	1
4.	3	0	-1
5.	-1	1	1
6.	0	-3	-1
7.	-1	-1	1
8.	-3	0	-1

(iv) For the *dual* perceptron algorithm, what is the α vector after the first weight update?

(v) What is the second misclassified point?

(vi) For the *primal* perceptron algorithm, what is the weight vector after the second weight update?

(vii) For the *dual* perceptron algorithm, what is the α vector after the second weight update?

(b) Consider the following kernel function: $K(\mathbf{x}, \mathbf{y}) = (\mathbf{x} \cdot \mathbf{y})^2$ where $\mathbf{x}, \mathbf{y} \in \mathbb{R}^2$. Find a valid Φ map for this kernel. That is, find a vector-to-vector function ϕ such that $\phi(\mathbf{x}) \cdot \phi(\mathbf{y}) = K(\mathbf{x}, \mathbf{y}) = (\mathbf{x} \cdot \mathbf{y})^2$. Show work to have a chance at receiving partial credit. Any precise answer format is acceptable.

- (c) We have n data points, $\{(x_i, y_i)\}_{i=1}^n$, with $x_i \in \mathbb{R}^d$ and $y_i \in \{1, 2, \dots, M\}$. That is, they are labelled as belonging to one of M classes. We will run the multiclass perceptron algorithm with an RBF kernel:

$$K(x_i, x_j) = \exp(- \| x_i - x_j \|^2) \tag{1}$$

Denote the dual weights at time t as $\alpha_y^{(t)} = (\alpha_{y,1}^{(t)}, \dots, \alpha_{y,K}^{(t)})$ for all classes $y = 1, \dots, M$.

- (i) What is the right value for K , the dimension of each of the dual weight vectors?

- | | |
|----------------------------|-------------------------------|
| <input type="radio"/> n | <input type="radio"/> M |
| <input type="radio"/> Mn | <input type="radio"/> $M + n$ |

- (ii) Assume that for some t , and for all y , $\alpha_y^{(t)}$ has only one nonzero entry. This single nonzero entry equals one. All the nonzero entries occur at different indices for different y . Describe the decision regions in \mathcal{R}^d for the M classes in terms of distances between points.

Q2. Decision Trees

You are given a dataset for training a decision tree. The goal is to predict the label (+ or -) given the features A, B, and C.

A	B	C	label
0	0	0	+
0	0	1	+
0	1	0	+
0	1	1	-
1	0	0	-
1	0	1	-
1	1	0	+
1	1	1	-

First, consider building a decision tree by greedily splitting according to information gain.

(a) Which features could be at the root of the resulting tree? Select all possible answers.

- A
- B
- C

(b) How many edges are there in the longest path of the resulting tree? Select all possible answers.

- 1
- 2
- 3
- 4
- None of the above

Now, consider building a decision tree with the smallest possible height.

(c) Which features could be at the root of the resulting tree? Select all possible answers.

- A
- B
- C

(d) How many edges are there in the longest path of the resulting tree? Select all possible answers.

- 1
- 2
- 3
- 4
- None of the above