


## Q1. Machine Learning: Potpourri

- (a) What is the **minimum** number of parameters needed to fully model a joint distribution  $P(Y, F_1, F_2, \dots, F_n)$  over label  $Y$  and  $n$  features  $F_i$ ? Assume binary class where each feature can possibly take on  $k$  distinct values.
- (b) Under the **Naive Bayes assumption**, what is the **minimum** number of parameters needed to model a joint distribution  $P(Y, F_1, F_2, \dots, F_n)$  over label  $Y$  and  $n$  features  $F_i$ ? Assume binary class where each feature can take on  $k$  distinct values.
- (c) You suspect that you are overfitting with your Naive Bayes with Laplace Smoothing. How would you adjust the strength  $k$  in Laplace Smoothing?
- Increase  $k$   Decrease  $k$
- (d) While using Naive Bayes with Laplace Smoothing, increasing the strength  $k$  in Laplace Smoothing can:
- Increase training error  Decrease training error  
 Increase validation error  Decrease validation error
- (e) It is possible for the perceptron algorithm to never terminate on a dataset that is linearly separable in its feature space.
- True  False
- (f) If the perceptron algorithm terminates, then it is guaranteed to find a max-margin separating decision boundary.
- True  False
- (g) In binary perceptron where the initial weight vector is  $\vec{0}$ , the final weight vector can be written as a linear combination of the training data feature vectors.
- True  False
- (h) For binary class classification, logistic regression produces a linear decision boundary.
- True  False
- (i) In the binary classification case, logistic regression is exactly equivalent to a single-layer neural network with a sigmoid activation and the cross-entropy loss function.
- True  False
- (j) You train a linear classifier on 1,000 training points and discover that the training accuracy is only 50%. Which of the following, if done in isolation, has a good chance of improving your training accuracy?
- Add novel features  Train on more data
- (k) You now try training a neural network but you find that the training accuracy is still very low. Which of the following, if done in isolation, has a good chance of improving your training accuracy?
- Add more hidden layers  Add more units to the hidden layers

# Q2. Neural Networks: Representation



For each of the piecewise-linear functions below, mark all networks from the list above that can represent the function **exactly** on the range  $x \in (-\infty, \infty)$ . In the networks above, *relu* denotes the element-wise ReLU nonlinearity:  $relu(z) = \max(0, z)$ . The networks  $G_i$  use 1-dimensional layers, while the networks  $H_i$  have some 2-dimensional intermediate layers.

