

61A Lecture 9

Announcements

Data Abstraction

Data Abstraction

Data Abstraction

- Compound values combine other values together

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- Data abstraction: A methodology by which functions enforce an abstraction barrier between **representation** and **use**

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- Data abstraction: A methodology by which functions enforce an abstraction barrier between **representation** and **use**

Data Abstraction

- Compound values combine other values together
 - A date: a year, a month, and a day
 - A geographic position: latitude and longitude
- Data abstraction lets us manipulate compound values as units
- Isolate two parts of any program that uses data:
 - How data are represented (as parts)
 - How data are manipulated (as units)
- Data abstraction: A methodology by which functions enforce an abstraction barrier between **representation** and **use**

All
Programmers

Great
Programmers

Rational Numbers

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Numbers

$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:

Constructor → `rational(n, d)` returns a rational number `x`

- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Numbers


$$\frac{\text{numerator}}{\text{denominator}}$$

Exact representation of fractions

A pair of integers

As soon as division occurs, the exact representation may be lost! (Demo)

Assume we can compose and decompose rational numbers:



Rational Number Arithmetic

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5}$$

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

Example

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy}$$

General Form

Rational Number Arithmetic

$$\frac{3}{2} * \frac{3}{5} = \frac{9}{10}$$

$$\frac{3}{2} + \frac{3}{5} = \frac{21}{10}$$

Example

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

General Form

Rational Number Arithmetic Implementation

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                    denom(x) * denom(y))
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational(numer(x) * numer(y),  
                   denom(x) * denom(y))
```

Constructor

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                    denom(x) * denom(y) )
```

Constructor

Selectors

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                   denom(x) * denom(y))
```

Constructor

Selectors

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                   denom(x) * denom(y))
```

Constructor

Selectors

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

```
def print_rational(x):  
    print(numer(x), '/', denom(x))
```

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Rational Number Arithmetic Implementation

```
def mul_rational(x, y):  
    return rational( numer(x) * numer(y),  
                    denom(x) * denom(y))
```

Constructor

Selectors

$$\frac{nx}{dx} * \frac{ny}{dy} = \frac{nx*ny}{dx*dy}$$

```
def add_rational(x, y):  
    nx, dx = numer(x), denom(x)  
    ny, dy = numer(y), denom(y)  
    return rational(nx * dy + ny * dx, dx * dy)
```

$$\frac{nx}{dx} + \frac{ny}{dy} = \frac{nx*dy + ny*dx}{dx*dy}$$

```
def print_rational(x):  
    print(numer(x), '/', denom(x))
```

```
def rationals_are_equal(x, y):  
    return numer(x) * denom(y) == numer(y) * denom(x)
```

- `rational(n, d)` returns a rational number `x`
- `numer(x)` returns the numerator of `x`
- `denom(x)` returns the denominator of `x`

These functions implement an abstract representation for rational numbers

Pairs

Representing Pairs Using Lists

Representing Pairs Using Lists

```
>>> pair = [1, 2]
```

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]

>>> x, y = pair
```

A list literal:
Comma-separated expressions in brackets

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]

>>> x, y = pair
>>> x
1
```

A list literal:
Comma-separated expressions in brackets

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

```
>>> x, y = pair
>>> x
1
>>> y
2
```

A list literal:
Comma-separated expressions in brackets

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

```
>>> x, y = pair
>>> x
1
>>> y
2
```

A list literal:
Comma-separated expressions in brackets

"Unpacking" a list

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

```
>>> x, y = pair
>>> x
1
>>> y
2
```

```
>>> pair[0]
1
```

A list literal:
Comma-separated expressions in brackets

"Unpacking" a list

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

```
>>> x, y = pair
>>> x
1
>>> y
2
```

```
>>> pair[0]
1
>>> pair[1]
2
```

A list literal:
Comma-separated expressions in brackets

"Unpacking" a list

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

```
>>> x, y = pair
>>> x
1
>>> y
2
```

```
>>> pair[0]
1
>>> pair[1]
2
```

A list literal:
Comma-separated expressions in brackets

"Unpacking" a list

Element selection using the selection operator

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

```
>>> x, y = pair
>>> x
1
>>> y
2
```

"Unpacking" a list

```
>>> pair[0]
1
>>> pair[1]
2
```

Element selection using the selection operator

```
>>> from operator import getitem
```

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

```
>>> x, y = pair
>>> x
1
>>> y
2
```

"Unpacking" a list

```
>>> pair[0]
1
>>> pair[1]
2
```

Element selection using the selection operator

```
>>> from operator import getitem
>>> getitem(pair, 0)
1
```


Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

```
>>> x, y = pair
>>> x
1
>>> y
2
```

"Unpacking" a list

```
>>> pair[0]
1
>>> pair[1]
2
```

Element selection using the selection operator

```
>>> from operator import getitem
>>> getitem(pair, 0)
1
>>> getitem(pair, 1)
2
```

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

```
>>> x, y = pair
>>> x
1
>>> y
2
```

"Unpacking" a list

```
>>> pair[0]
1
>>> pair[1]
2
```

Element selection using the selection operator

```
>>> from operator import getitem
>>> getitem(pair, 0)
1
>>> getitem(pair, 1)
2
```

Element selection function

Representing Pairs Using Lists

```
>>> pair = [1, 2]
>>> pair
[1, 2]
```

A list literal:
Comma-separated expressions in brackets

```
>>> x, y = pair
>>> x
1
>>> y
2
```

"Unpacking" a list

```
>>> pair[0]
1
>>> pair[1]
2
```

Element selection using the selection operator

```
>>> from operator import getitem
>>> getitem(pair, 0)
1
>>> getitem(pair, 1)
2
```

Element selection function

More lists next lecture

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

```
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

```
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Select item from a list

Representing Rational Numbers

```
def rational(n, d):  
    """Construct a rational number that represents N/D."""  
    return [n, d]
```

Construct a list

```
def numer(x):  
    """Return the numerator of rational number X."""  
    return x[0]
```

```
def denom(x):  
    """Return the denominator of rational number X."""  
    return x[1]
```

Select item from a list

(Demo)

Reducing to Lowest Terms

Example:

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:


$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2} \quad \frac{2}{5} + \frac{1}{10}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2} \qquad \frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$


$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

```
def rational(n, d):
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

```
    return [n//g, d//g]
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

Greatest common divisor

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

```
    return [n//g, d//g]
```

Reducing to Lowest Terms

Example:

$$\frac{3}{2} * \frac{5}{3} = \frac{5}{2}$$

$$\frac{2}{5} + \frac{1}{10} = \frac{1}{2}$$

$$\frac{15}{6} * \frac{1/3}{1/3} = \frac{5}{2}$$

$$\frac{25}{50} * \frac{1/25}{1/25} = \frac{1}{2}$$

```
from fractions import gcd
```

Greatest common divisor

```
def rational(n, d):
```

```
    """Construct a rational that represents n/d in lowest terms."""
```

```
    g = gcd(n, d)
```

```
    return [n//g, d//g]
```

(Demo)

Abstraction Barriers

Abstraction Barriers

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```


Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

two-element lists

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

two-element lists

list literals and element selection

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

two-element lists

list literals and element selection

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

two-element lists

list literals and element selection

Implementation of lists

Abstraction Barriers

Parts of the program that...

Treat rationals as...

Using...

Use rational numbers
to perform computation

whole data values

```
add_rational, mul_rational  
rationals_are_equal, print_rational
```

Create rationals or implement
rational operations

numerators and
denominators

```
rational, numer, denom
```

Implement selectors and
constructor for rationals

two-element lists

list literals and element selection

Implementation of lists

Violating Abstraction Barriers

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```


Violating Abstraction Barriers

Does not use
constructors

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

Violating Abstraction Barriers

Does not use
constructors

Twice!

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

Violating Abstraction Barriers

Does not use
constructors

Twice!

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):  
    return [ x[0] * y[1], x[1] * y[0] ]
```

No selectors!

Violating Abstraction Barriers

Does not use
constructors

Twice!

```
add_rational( [1, 2], [1, 4] )
```

```
def divide_rational(x, y):
```

```
    return [ x[0] * y[1], x[1] * y[0] ]
```

No selectors!

And no constructor!

Violating Abstraction Barriers

Data Representations

What is Data?

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

You can recognize an abstract data representation by its behavior

What is Data?

- We need to guarantee that constructor and selector functions work together to specify the right behavior
- Behavior condition: If we construct rational number x from numerator n and denominator d , then $\text{numer}(x)/\text{denom}(x)$ must equal n/d
- Data abstraction uses selectors and constructors to define behavior
- If behavior conditions are met, then the representation is valid

You can recognize an abstract data representation by its behavior

(Demo)

Rationals Implemented as Functions

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Rationals Implemented as Functions

```
def rational(n, d):
```

```
    def select(name):
```

```
        if name == 'n':
```

```
            return n
```

```
        elif name == 'd':
```

```
            return d
```

```
    return select
```

This function represents a rational number

```
def numer(x):
```

```
    return x('n')
```

```
def denom(x):
```

```
    return x('d')
```


Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Selector calls x

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')
```

```
def denom(x):  
    return x('d')
```

Selector calls x

```
x = rational(3, 8)  
numer(x)
```

Rationals Implemented as Functions

```
def rational(n, d):  
    def select(name):  
        if name == 'n':  
            return n  
        elif name == 'd':  
            return d  
    return select
```

This function represents a rational number

Constructor is a higher-order function

```
def numer(x):  
    return x('n')  
  
def denom(x):  
    return x('d')
```

Selector calls x

