

## Aggregation

## Announcements

## Aggregation

### Aggregate Functions

So far, all SQL expressions have referred to the values in a single row at a time

```
[expression] as [name], [expression] as [name], ...  
select [columns] from [table] where [expression] order by [expression];
```

An aggregate function in the [columns] clause computes a value from a group of rows

```
create table animals as  
select "dog" as kind, 4 as legs, 20 as weight union  
select "cat" , 4 , 10 union  
select "ferret" , 4 , 10 union  
select "parrot" , 2 , 6 union  
select "penguin" , 2 , 10 union  
select "t-rex" , 2 , 12000;
```

animals:

kind	legs	weight
dog	4	20
cat	4	10
ferret	4	10
parrot	2	6
penguin	2	10
t-rex	2	12000

```
select max(legs) from animals;
```

max(legs)
4

 (Demo)

### Mixing Aggregate Functions and Single Values

An aggregate function also selects some row in the table to supply the values of columns that are not aggregated. In the case of max or min, this row is that of the max or min value. Otherwise, it is arbitrary.

```
select max(weight), kind from animals;      select max(legs), kind from animals;  
select min(kind), kind from animals;      select avg(weight), kind from animals;
```

(Demo)

```
create table animals as  
select "dog" as kind, 4 as legs, 20 as weight union  
select "cat" , 4 , 10 union  
select "ferret" , 4 , 10 union  
select "parrot" , 2 , 6 union  
select "penguin" , 2 , 10 union  
select "t-rex" , 2 , 12000;
```

animals:

kind	legs	weight
dog	4	20
cat	4	10
ferret	4	10
parrot	2	6
penguin	2	10
t-rex	2	12000

### Discussion Question

What are all the kinds of animals that have the maximal number of legs?

## Groups

### Grouping Rows

Rows in a table can be grouped, and aggregation is performed on each group

```
[expression] as [name], [expression] as [name], ...  
select [columns] from [table] group by [expression] having [expression];
```

The number of groups is the number of unique values of an expression

```
select legs, max(weight) from animals group by legs;
```

legs	max(weight)
4	20
2	12000

(Demo)

animals:

kind	legs	weight
dog	4	20
cat	4	10
ferret	4	10
parrot	2	6
penguin	2	10
t-rex	2	12000

## Selecting Groups

Rows in a table can be grouped, and aggregation is performed on each group

```
[expression] as [name], [expression] as [name], ...
```

```
select [columns] from [table] group by [expression] having [expression];
```

A `having` clause filters the set of groups that are aggregated

```
select weight/legs, count(*) from animals group by weight/legs having count(*)>1;
```

weight/legs	count(*)
5	2
2	2

weight/legs=5  
weight/legs=2  
weight/legs=2  
weight/legs=3  
weight/legs=5  
weight/legs=6000

animals:

kind	legs	weight
dog	4	20
cat	4	10
ferret	4	10
parrot	2	6
penguin	2	10
t-rex	2	12000

## Discussion Question

What's the maximum difference between leg count for two animals with the same weight?

Example: Big Game

(Demo)