

Containers

Announcements

Lists

['Demo']

Working with Lists

```
>>> digits = [1, 8, 2, 8]           >>> digits = [2//2, 2+2+2+2, 2, 2*2*2]
The number of elements
>>> len(digits)
4
An element selected by its index
>>> digits[3]                       >>> getitem(digits, 3)
8                                    8
Concatenation and repetition
>>> [2, 7] + digits * 2              >>> add([2, 7], mul(digits, 2))
[2, 7, 1, 8, 2, 8, 1, 8, 2, 8]    [2, 7, 1, 8, 2, 8, 1, 8, 2, 8]
Nested lists
>>> pairs = [[10, 20], [30, 40]]
>>> pairs[1]
[30, 40]
>>> pairs[1][0]
30
```

Containers

Containers

Built-in operators for testing whether an element appears in a compound value

```
>>> digits = [1, 8, 2, 8]
>>> 1 in digits
True
>>> 8 in digits
True
>>> 5 not in digits
True
>>> not(5 in digits)
True
```

(Demo)

For Statements

(Demo)

Sequence Iteration

```
def count(s, value):
    total = 0
    for element in s:
        if element == value:
            total = total + 1
    return total
```

Name bound in the first frame
of the current environment
(not a new frame)

For Statement Execution Procedure

```
for <name> in <expression>:  
    <suite>
```

1. Evaluate the header <expression>, which must yield an iterable value (a sequence)
2. For each element in that sequence, in order:
 - A. Bind <name> to that element in the current frame
 - B. Execute the <suite>

Sequence Unpacking in For Statements

A sequence of fixed-length sequences

```
>>> pairs = [(1, 2), (2, 2), (3, 2), (4, 4)]  
>>> same_count = 0
```

A name for each element in a fixed-length sequence

Each name is bound to a value, as in multiple assignment

```
>>> for x, y in pairs:  
...     if x == y:  
...         same_count = same_count + 1  
>>> same_count  
2
```

Ranges

The Range Type

A range is a sequence of consecutive integers.*

..., -5, -4, -3, -2, -1, 0, 1, 2, 3, 4, 5, ...

range(-2, 2)

Length: ending value - starting value

(Demo)

Element selection: starting value + index

```
>>> list(range(-2, 2))  
[-2, -1, 0, 1]
```

List constructor

```
>>> list(range(4))  
[0, 1, 2, 3]
```

Range with a 0 starting value

* Ranges can actually represent more general integer sequences.

Recursive Sums

Sum (recursively)

```
def mysum(L):  
    if (L == []):  
        return 0  
    else:  
        return L[0] + mysum(L[1:])
```

```
mysum([2, 4, 1, 5])  
2 + mysum([4, 1, 5])  
4 + mysum([1, 5])  
1 + mysum([5])  
5 + mysum([])  
0
```

```
# --- DRILL ---  
# Write an iterative function that takes input  
# integer "n" and returns the sum of the first "n"  
# integers: sum(5) returns 1+2+3+4+5
```

```
# --- DRILL ---  
# Write an iterative function that takes input  
# integer "n" and returns the sum of the first "n"  
# integers: sum(5) returns 1+2+3+4+5
```

```
def sum_iter(n):  
    sum = 0  
    for i in range(0, n+1):  
        sum = sum + i  
  
    return( sum )
```

```
# --- DRILL ---
# Write a recursive function that takes as input
# integer "n" and returns the sum of the first "n"
# integers: sum(5) returns 1+2+3+4+5
```

```
# --- DRILL ---
# Write a recursive function that takes as input
# integer "n" and returns the sum of the first "n"
# integers: sum(5) returns 1+2+3+4+5
```

```
def sum_rec(n):
    if( n == 0 ):
        return(0)
    else:
        return n + sum_rec(n-1)
```

List Comprehensions

```
>>> letters = ['a', 'b', 'c', 'd', 'e', 'f', 'm', 'n', 'o', 'p']
>>> [letters[i] for i in [3, 4, 6, 8]]
```

```
['d', 'e', 'm', 'o']
```

List Comprehensions

```
[<map exp> for <name> in <iter exp> if <filter exp>]
```

Short version: [<map exp> for <name> in <iter exp>]

A combined expression that evaluates to a list using this evaluation procedure:

1. Add a new frame with the current frame as its parent
2. Create an empty *result* list that is the value of the expression
3. For each element in the iterable value of <iter exp>:
 - A. Bind <name> to that element in the new frame from step 1
 - B. If <filter exp> evaluates to a true value, then add the value of <map exp> to the result list

Strings

Strings are an Abstraction

Representing data:

```
'200'    '1.2e-5'    'False'    '[1, 2]'
```

Representing language:

```
"""And, as imagination bodies forth
The forms of things unknown, the poet's pen
Turns them to shapes, and gives to airy nothing
A local habitation and a name.
"""
```

Representing programs:

```
'curry = lambda f: lambda x: lambda y: f(x, y)'
```

(Demo)

String Literals Have Three Forms

```
>>> 'I am string!'
'I am string!'

>>> "I've got an apostrophe"
"I've got an apostrophe"

>>> '您好'
'您好'

>>> """The Zen of Python
claims, Readability counts.
Read more: import this."""
'The Zen of Python\nclaims, Readability counts.\nRead more: import this.'
```

Single-quoted and double-quoted strings are equivalent

A backslash "escapes" the following character

"Line feed" character represents a new line

Reversing a String

Reversing a List (recursively)

```
reverse("ward") = "draw"  
reverse("ward") = reverse("ard") + "w"  
reverse("ard") = reverse("rd") + "a"  
reverse("rd") = reverse("d") + "r"  
reverse("d") = "d"
```

Reversing a List (recursively)

```
reverse("ward") = "draw"  
reverse("ward") = reverse("ard") + "w"  
reverse("ard") = "d" + "r" + "a"
```

Reversing a List (recursively)

```
def reverse(s):  
    if len(s) == 1:  
        return s  
    else:  
        return reverse(s[1:]) + s[0]
```