

## Lecture #8: More on Functions

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 1

## Another Recursion Problem: Counting Partitions

- I'd like to know the number of distinct ways of expressing an integer as a sum of positive integer "parts."
- To make things more interesting, let's also limit the size of the integer parts to some given value:

```
def num_partitions(n, k):  
    """Number of distinct ways to express N as a sum of positive  
    integers each of which is <= K, where K > 0. (The empty sum is 0.)"""
```

- Example:

```
x06 = 3+3  
    = 3+2+1  
    = 3+1+1+1  
    = 2+2+2  
    = 2+2+1+1  
    = 2+1+1+1+1  
    = 1+1+1+1+1+1
```

so num\_partitions(6, 3) is 7.

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 2

## Identifying the Problem in the Problem

- Again, consider num\_partitions(6, 3).
- Some partitions will contain the maximum size integer, 3, and the rest won't.
- Those that do contain 3 then have various ways to partition the remaining 3.  
3 + 3  
3 + 2 + 1  
3 + 1 + 1 + 1
- While those that do not contain 3 partition 6 using integers no larger than 2:  
2 + 2 + 2  
2 + 2 + 1 + 1  
2 + 1 + 1 + 1 + 1  
1 + 1 + 1 + 1 + 1 + 1
- These observations generalize, and lead immediately to a solution.

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 3

## Counting Partitions: Code (I)

```
def num_partitions(n, k):  
    """Number of distinct ways to express N as a sum of positive  
    integers each of which is <= K, where K > 0. (The empty sum is 0.)"""  
    if _____:  
        return 0  
    elif _____:  
        return 1  
    else:  
        return _____;
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 4

## Counting Partitions: Code (II)

```
def num_partitions(n, k):  
    """Number of distinct ways to express N>=0 as a sum of positive  
    integers each of which is <= K, where K > 0. (The empty sum is 0.)"""  
    if n < 0:  
        return 0  
    elif _____:  
        return 1  
    else:  
        return _____;
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 5

## Counting Partitions: Code (III)

```
def num_partitions(n, k):  
    """Number of distinct ways to express N>=0 as a sum of positive  
    integers each of which is <= K, where K > 0. (The empty sum is 0.)"""  
    if n < 0:  
        return 0  
    elif k == 1 or n <= 1:  
        return 1  
    else:  
        return _____;
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 6

## Counting Partitions: Code (IV)

```
def num_partitions(n, k):
    """Number of distinct ways to express N>=0 as a sum of positive
    integers each of which is <= K, where K > 0. (The empty sum is 0.)"""
    if n < 0:
        return 0
    elif k == 1 or n <= 1:
        return 1
    else:
        return num_partitions(n - k, k) + num_partitions(n, k - 1)
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 7

## Functions and Data

- We tend to think of functions as simply doing or computing something with data.
- In fact, they can also represent or contain data themselves.
- Trivial example:

```
>>> def const(n):
...     return lambda: n
>>> x, y = const(5), const(11)
>>> print(x(), y())
5 11
```
- The functions returned by `const` contain pointers to the local frames created when `const` was called, which in turn contain copies of the argument values (5 and 11).

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 8

## Functions and Data (II)

- We can get a bit fancier:

```
>>> def cons(left, right):
...     return lambda which: left if which else right
>>> p = cons("value", 42)
>>> print(P(True), P(False))
value 42
>>> l = cons(1, cons(2, cons(3, None)))
>>> print(L(True), L(False)(True), L(False)(False)(True),
...       L(False)(False)(False))
1 2 3 None
```

(See the chain example at the end of Lecture #4.)

- So, in effect, values returned by `cons` are lists of values.

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 9

## The Pair Abstraction

- However, writing `P(True)` for “the left part of `P`” is not the clearest code one could imagine.
- Better to express the programmer’s intent:

```
>>> def cons(left, right):
...     return lambda which: left if which else right
>>> def left(pair): return pair(True)
>>> def right(pair): return pair(False)
>>> p = cons("value", 42)
>>> print(left(p), right(p))
value 42
```
- Together, these three functions define a *data type*.
- The data (pairs) are *represented* by functions returned by `cons`.
- `left` and `right` are the basic operations on the data type.
- If we use these `cons`, `left`, and `right` and three functions and ignore the fact that `cons` really produces a function rather than a pair, we are obeying the *abstraction barrier*.

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 10

## Data Abstraction Philosophy

- In the old days, one described programs as hierarchies of actions: *procedural decomposition*.
- Starting in the 1970’s, emphasis moved to the data that the functions operate on.
- An *abstract data type (ADT)* (like the pair abstraction) represents some kind of thing and the operations upon it.
- Instances of the type are often generically called *objects*.
- We can usefully organize our programs around the ADTs in them.
- For each type, we define an *interface* that describes for users (“clients”) of that type of data what operations are available.
- Typically, the interface consists of functions.
- The collection of specifications (syntactic and semantic—see lecture #6) constitute a *specification of the type*.
- We call ADTs *abstract* because clients ideally need not know internals.

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 11

## Rational Numbers

- The book uses “rational number” as an example of an ADT:

```
def make_rat(n, d):
    """The rational number n/d, assuming n, d are integers, d!=0"""
def add_rat(x, y):
    """The sum of rational numbers x and y."""
def mul_rat(x, y):
    """The product of rational numbers x and y."""
def numer(x):
    """The numerator of rational number x."""
def denom(x):
    """The denominator of rational number x."""
```
- These definitions pretend that `x`, `y`, and `x` really are rational numbers.
- But from this point of view, the definitions of `numer` and `denom` are problematic. Why?

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 12

## A Better Specification

- Problem is that "the numerator (denominator) of  $r$ " is not well-defined for a rational number.
- If `make_rat` really produced rational numbers, then `make_rat(2, 4)` and `make_rat(1, 2)` ought to be identical. So should `make_rat(1, -1)` and `make_rat(-1, 1)`.
- So a better specification would be

```
def numer(r):  
    """The numerator of rational number r in lowest terms."""  
  
def denom(r):  
    """The denominator of rational number r in lowest terms.  
    Always positive."""
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 13

## Rationals as Pairs (I)

- Our pair abstraction (represented by functions) can in turn represent rational numbers.

```
from math import gcd # Need Python3.5 actually.  
  
def make_rat(n, d):  
    """The rational number n/d, assuming n, d are integers, d!=0"""  
    g = gcd(n, d) if d > 0 else -gcd(n, d)  
    n //= g; d //= g  
    return cons(n, d)  
  
def numer(r):  
    """The numerator of rational number r."""  
    return left(r)  
  
def denom(r):  
    """The denominator of rational number r."""  
    return right(r)  
  
def add_rat(x, y):  
    """The sum of rational numbers x and y."""  
    return 2  
  
def mul_rat(x, y):  
    """The product of rational numbers x and y."""  
    return 2
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 14

## Representation as Functions (II)

- One possibility for `add_rat`:

```
from math import gcd  
  
def make_rat(n, d):  
    """The rational number n/d, assuming n, d are integers, d!=0"""  
    g = gcd(n, d) if d > 0 else -gcd(n, d)  
    n //= g; d //= g  
    return lambda flag: n if flag == 0 else d  
    ...  
  
def add_rat(x, y):  
    n0, n1, d0, d1 = x(0), x(1), y(0), y(1)  
    n, d = n0 * d1 + n1 * d0, d0 * d1  
    g = gcd(n, d) if d > 0 else -gcd(n, d)  
    n //= g; d //= g  
    return lambda flag: n if flag == 0 else d
```

- Comments?

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 15

## Abstraction Violations and DRY

- Having created an abstraction (`make_rat`, `numer`, `denom`), use it:
  - Then, later changes of representation will affect less code.
  - Code will be clearer, since well-chosen names in the API make intent clear.

```
...  
  
def add_rat(x, y):  
    return make_rat(numer(x) * denom(y) + numer(y) * denom(x),  
                    denom(x) * denom(y))  
  
def mul_rat(x, y):  
    """The product of rational numbers x and y."""  
    return make_rat(numer(x) * numer(y), denom(x) * denom(y))
```

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 16

## Changing Representations

- It's cute that functions can represent pairs (or anything else, for that matter), but it's not a particularly efficient use of the them.
- Suppose that we instead decide to use Python's tuples. What changes?  

```
def cons(left, right):  
    return (left, right)  
def left(pair): return pair[0]  
def right(pair): return pair[1]
```
- Crucial Observation: Nothing else changes!

Last modified: Sun Feb 19 15:44:29 2017

CS61A, Lecture #8 17