

Lecture #21: Exceptional Conditions

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 1

Failed preconditions

- Part of the contract between the implementor and client is the set of *preconditions* under which a function, method, etc. is supposed to operate.

- Example:

```
class Rational:
    def __init__(self, x, y):
        """The rational number x/y. Assumes that x and y
        are ints and y != 0."""
```

- Here, "x and y are ints and y!=0" is a precondition on the client.
- So what happens when the precondition is not met?

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 2

Programmer Errors

- Python has preconditions of its own.
- Eg., type rules on operations: `3 + (2, 1)` is invalid.
- What happens when we (programmers) violate these preconditions?

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 3

Outside Events

- Some operations may entail the possibility of errors caused by the data or the environment in which a program runs.
- I/O over a network is a common example: connections go down; data is corrupted.
- User input is another major source of error: we may ask to read an integer numeral, and be handed something non-numeric.
- Again, what happens when such errors occur?

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 4

Possible Responses

- One approach is to take the point of view that when a precondition is violated, all bets are off and the implementor is free to do anything.
 - Corresponds to a logical axiom: False \Rightarrow True.
 - But not a particularly helpful or safe approach.
- One can adopt a convention in which erroneous operations return special error values.
 - Feasible in Python, but less so in languages that require specific types on return values.
 - Used in the C library, but can't be used for non-integer-returning functions.
 - Error prone (too easy to ignore errors).
- Cluttered (reader is forced to wade through a lot of error-handling code, a distraction from the main algorithm).
- Numerous programming languages, including Python, support a general notion of *exceptional condition* or *exception* with supporting syntax and semantics that separate error handling from main program logic.

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 5

Assertions

- The Python **assert** statement provides a standard way to check for *programmer* errors.
- Two forms:

```
assert CONDITION, DESCRIPTION
assert CONDITION, DESCRIPTION
```
- Equivalent to either

```
if _debug_ and not CONDITION:
    raise AssertionError
if _debug_ and not CONDITION:
    raise AssertionError(DESCRIPTION)
```
- By default, `__debug__` is true; **python3 -O...** makes it false.
- Because it can be turned off, this is not appropriate for detection of user errors, or other errors that the program is deliberately designed to handle.

Last modified: Thu Mar 16 16:52:48 2017

CS61A, Lecture #21 6

Exceptions

- An *exception mechanism* is a control structure that
 - Halts execution at one point in a program (called *raising* or *throwing* an exception).
 - Resumes execution at some other, previously designated point in the program (called *catching* or *handling* an exception).
- In Python, the `raise` statement raises (or *throws* exceptions, and the `try` statement catches them.

```
def fo(...):
    try:
        go(...)
    OTHER STUFF
    except:
        handle oops
def gl(...):
    if detectError():
        raise Dops()
MORE
# 1. Call of go...
# Skipped
# 4. Handle problem
# 2. Called by go, possibly many calls down
# 3. Raise exception
# Skipped
```

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 7

Standard Exceptions

- Exceptions are objects of builtin class `BaseException` or a subtype of it.
- The Python language and its library uses several predefined subclasses, such as:
 - `TypeError` A value has the wrong type for an operation.
 - `IndexError` Out-of-bounds list or tuple index (e.g.).
 - `KeyError` Nonexistent key to dictionary
 - `ValueError` Other inappropriate values of the right type.
 - `AssertionError` An `assert` statement with a false assertion.
 - `IOError` Non-existent file, e.g.
 - `OSError` Bad operand to an operating-system call.

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 8

Communicating the Reason

- Normally, the handler would like to know the reason for an exception.
- "Reason," being a noun, suggests we use objects, which is what Python does.
- Python defines the class `BaseException`. It or any subclass of it may convey information to a handler. We'll call these *exception classes*.
- `BaseException` carries arbitrary information as if declared:

```
class BaseException:
    def __init__(self, *args):
        self.args = args
    ...
    raise ValueError("x must be positive", x, y)
    raise ValueError          # Short for raise ValueError()
    e = ValueError("exceptions are just objects!")
    raise e                  # So this works, too
```

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 9

- The `raise` statement then packages up and sends information to a handler:

```
try:
    assorted statements
except ValueError as exc:
    print("Something was wrong with the arguments: {0}".format(exc))
```

- So far, we've just looked at exception *types*.
- To get at the exception objects, use a bit more syntax:

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 11

Handlers

- A function indicates that something is wrong: it is the client (caller) that decides what to do about it.
- The `try` statement allows one to provide one or more handlers for a set of statements, with selection based on the type of exception object thrown.

```
try:
    assorted statements
except ValueError:
    print("Something was wrong with the arguments")
except EnvironmentError: # Also catches subtypes IOError, OSError
    print("The operating system is telling us something")
except:
    print("Something wrong")
```

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 10

Cleaning Up and Reraising

- Sometimes we catch an exception in order to clean things up before the real handler takes over.

```
try:
    inp = open(fileName)
except:
    assorted processing
    inp.close()
    raise
    # Reraise the same exception
```

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 12

Finally Clauses

- More generally, we can clean things up regardless of how we leave the **try** statement:

```
for i in range(100):
    try:
        setTimer(10) # Set time limit
        if found(1):
            break
    LongComputationThatKillsTimeOut()
finally:
    cancelTimer()
# Continue with 'break' or with exception
```

- This fragment will always cancel the timer, whether the loop ends because of **break** or a timeout exception.
- After which, it carries on whatever caused the **try** to stop.

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 13

"With" Clauses

- The **finally** statement comes in useful in a number of standard places, such as generally
 - When the program reserves some **resource** for its use from a small set of such resources, and must be sure to return it to prevent deadlocking the system.
 - When the program creates some kind of persistent object (like a file) that requires some specific action before it is complete.
- Such situations are sufficiently common that Python's designers decided to provide a more concise and general construct to handle them.
- Just as **for** statements and generator definitions are associated with particular kinds of object type—iterator and iterables—this new construct is associated with a kind of object known as a **context manager**.

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 14

Example

- If you really want to be tidy about using a file, you need the following pieces, at least:

```
def writeAll(filename, text):
    """Create (or overwrite) a file named filename with the string TEXT."""
    try:
        out = open(filename, "w") # Open for writing
        out.write(text)
    finally:
        out.close() # Make sure everything is written

def writeAll(filename, text):
    """Create (or overwrite) a file named filename with the string TEXT."""
    with open(filename, "w") as out:
        out.write(text)
```

- This can be effected concisely with
- This is because Python files (returned by open) implement the methods required to be context managers: `__enter__` and `__exit__`.

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 15

With-Statement Details (Simplified)

- The statement
- ```
with E1 as VAR:
 STATEMENTS
```

is essentially the same as

```
mgr = E1
VAR = mgr.__enter__()
ok = True
try:
 STATEMENTS
except:
 ok = False
 if not mgr.__exit__(info about the exception):
 raise # Re-raise the exception
finally:
 if ok:
 mgr.__exit__(None, None, None)
```

- [WARNING: This is not entirely correct, being simplified, but it gives the general idea.]

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 16

## Other Uses of Exceptions

- We've described a software-engineering motivation for exceptions: dealing with erroneous conditions.
- But from a programming-language point of view, they're just another control structure.
- Python uses them in non-erroneous situations as well:
  - We've seen that **iterators** use `StopIteration` to indicate they have no more elements.
  - Alternatively, Python can create an iterator out of any object that has a `__getitem__` method, which (as usual) raises `IndexError` to indicate the end of a sequence.

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 17

## Summary

- Exceptions are a way of returning information from a function "out of band", and allowing programmers to clearly separate error handling from normal cases.
- In effect, specifying possible exceptions is therefore part of the interface.
- Usually, the specification is implicit: one assumes that violation of a precondition might cause an exception.
- When a particular exception indicates something that might normally arise (e.g., bad user input), it will often be mentioned explicitly in the documentation of a function.
- Finally, **raise** and **try** may be used purely as normal control structures. By convention, the exceptions used in this case don't end in "Error."

Last modified: Thu Mar 16 16:52:45 2017

CS61A, Lecture #21 18