

CS 61A
Lab assignment 3A
For 7/10/06

1. Try these in Scheme:

```
(define x (cons 4 5))

(car x)

(cdr x)

(define y (cons 'hello 'good bye))

(define z (cons x y))

(car (cdr z))

(cdr (cdr z))
```

2. Predict the result of each of these before you try it:

```
(cdr (car z))
(car (cons 8 3))
(car z)
(car 3)
```

3. Enter these definitions into Scheme:

```
(define (make-rational num den)
  (cons num den))
(define (numerator rat)
  (car rat))
(define (denominator rat)
  (cdr rat))
(define (*rat a b)
  (make-rational (* (numerator a) (numerator b))
                 (* (denominator a) (denominator b))))
(define (print-rat rat)
  (word (numerator rat) '/ (denominator rat)))
```

4. Try this:

```
(print-rat (make-rational 2 3))
(print-rat (*rat (make-rational 2 3) (make-rational 1 4)))
```

5. Define a procedure `+rat` to add two rational numbers, in the same style as `*rat` above.

6. Now do exercises 2.2, 2.3, and 2.4 from SICP.

7. SICP ex. 2.18; this should take some thought, and you should make sure you get it right, but don't get stuck on it for the whole hour. Note: Your solution should reverse lists, not sentences! That is, you should be using `cons`, `car`, and `cdr`, not `first`, `sentence`, etc.