




Higher-Order Functions

Generalizing Patterns with Arguments

Regular geometric shapes relate length and area.

Shape:



Area:

$$1 \cdot r^2$$

$$\pi \cdot r^2$$

$$\frac{3\sqrt{3}}{2} \cdot r^2$$

Finding common structure allows for shared implementation

(Demo)

Generalizing Over Computational Processes

The common structure among functions may be a computational process, rather than a number.

$$\sum_{k=1}^5 k = 1 + 2 + 3 + 4 + 5 = 15$$

$$\sum_{k=1}^5 k^3 = 1^3 + 2^3 + 3^3 + 4^3 + 5^3 = 225$$

$$\sum_{k=1}^5 \frac{8}{(4k-3) \cdot (4k-1)} = \frac{8}{3} + \frac{8}{35} + \frac{8}{99} + \frac{8}{195} + \frac{8}{323} = 3.04$$

(Demo)

Summation Example

```
def cube(k):  
    return pow(k, 3)
```

Function of a single argument
(*not* called "term")

```
def summation(n, term):  
    """Sum the first n terms of a sequence.
```

A formal parameter that will
be bound to a function

```
>>> summation(5, cube)
```

```
225
```

The cube function is passed
as an argument value

```
    """  
    total, k = 0, 1  
    while k <= n:  
        total, k = total + term(k), k + 1  
    return total
```

0 + 1 + 8 + 27 + 64 + 125

The function bound to term
gets called here

Functions as Return Values

(Demo)

Locally Defined Functions

Functions defined within other function bodies are bound to names in a local frame

A function that
returns a function


```
def make_adder(n):  
    """Return a function that takes one argument k and returns k + n.  
  
    >>> add_three = make_adder(3)  
    >>> add_three(4)  
    7  
    """  
    def adder(k):  
        return k + n  
    return adder
```

The name add_three is bound
to a function

A def statement within
another def statement

Can refer to names in the
enclosing function


Call Expressions as Operator Expressions




Function Example: Sounds

WAV Files

The Waveform Audio File Format encodes a sampled sound wave



A triangle wave is the simple wave form with the most pleasing sound



(Demo)

Function Composition

(Demo)


The Environment Diagram for Function Composition

```

1 def square(x):
2     return x * x
3
4 def make_adder(n):
5     def adder(k):
6         return k + n
7     return adder
8
9 def compose1(f, g):
10    def h(x):
11        return f(g(x))
12    return h
13
14 compose1(square, make_adder(2))(3)

```

Return value of make_adder is an argument to compose1



Abstraction

Functional Abstractions

```
def square(x):  
    return mul(x, x)
```

```
def sum_squares(x, y):  
    return square(x) + square(y)
```

What does `sum_squares` need to know about `square`?

- Square takes one argument. **Yes**
- Square has the intrinsic name `square`. **No**
- Square computes the square of a number. **Yes**
- Square computes the square by calling `mul`. **No**

```
def square(x):  
    return pow(x, 2)
```

```
def square(x):  
    return mul(x, x-1) + x
```

If the name “`square`” were bound to a built-in function, `sum_squares` would still work identically.

Choosing Names

Names typically don't matter for correctness

but

they matter a lot for composition

From:	To:
true_false	rolled_a_one
d	dice
helper	take_turn
my_int	num_rolls
l, I, 0	k, i, m

Names should convey the meaning or purpose of the values to which they are bound.

The type of value bound to the name is best documented in a function's docstring.

Function names typically convey their effect (**print**), their behavior (**triple**), or the value returned (**abs**).

Which Values Deserve a Name


Reasons to add a new name

Repeated compound expressions:

```
if sqrt(square(a) + square(b)) > 1:  
    x = x + sqrt(square(a) + square(b))
```



```
hypotenuse = sqrt(square(a) + square(b))  
if hypotenuse > 1:  
    x = x + hypotenuse
```



Meaningful parts of complex expressions:

```
x1 = (-b + sqrt(square(b) - 4 * a * c)) / (2 * a)
```



```
discriminant = square(b) - 4 * a * c  
x1 = (-b + sqrt(discriminant)) / (2 * a)
```

More Naming Tips

- Names can be long if they help document your code:

```
average_age = average(age, students)
```

is preferable to

```
# Compute average age of students  
aa = avg(a, st)
```

- Names can be short if they represent generic quantities: counts, arbitrary functions, arguments to mathematical operations, etc.

n, k, i - Usually integers

x, y, z - Usually real numbers

f, g, h - Usually functions