

*Note this worksheet is very long and is not expected to be finished in an hour.*

## 1 Athletes

Suppose we have the Person, Athlete, and SoccerPlayer classes defined below.

```
1 class Person {
2     void speakTo(Person other) { System.out.println("kudos"); }
3     void watch(SoccerPlayer other) { System.out.println("wow"); }
4 }
5
6 class Athlete extends Person {
7     void speakTo(Athlete other) { System.out.println("take notes"); }
8     void watch(Athlete other) { System.out.println("game on"); }
9 }
10
11 class SoccerPlayer extends Athlete {
12     void speakTo(Athlete other) { System.out.println("respect"); }
13     void speakTo(Person other) { System.out.println("hmph"); }
14 }
```

- (a) For each line below, write what, if anything, is printed after its execution. Write CE if there is a compiler error and RE if there is a runtime error. If a line errors, continue executing the rest of the lines.

```
1 Person itai = new Person();
2
3 SoccerPlayer shivani = new Person();
4
5 Athlete sohum = new SoccerPlayer();
6
7 Person jack = new Athlete();
8
9 Athlete anjali = new Athlete();
10
11 SoccerPlayer chirasree = new SoccerPlayer();
12
13 itai.watch(chirasree);
14
15 jack.watch(sohum);
16
17 itai.speakTo(sohum);
18
19 jack.speakTo(anjali);
```

```
20
21 anjali.speakTo(chirasree);
22
23 sohum.speakTo(itai);
24
25 chirasree.speakTo((SoccerPlayer) sohum);
26
27 sohum.watch(itai);
28
29 sohum.watch((Athlete) itai);
30
31 ((Athlete) jack).speakTo(anjali);
32
33 ((SoccerPlayer) jack).speakTo(chirasree);
34
35 ((Person) chirasree).speakTo(itai);
```

- (b) You may have noticed that `jack.watch(sohum)` produces a compile error. Interestingly, we can resolve this error by **adding casting!** List two fixes that would resolve this error. The first fix should print `wow`. The second fix should print `game on`. Each fix may cast either `jack` or `sohum`.

- 1.
- 2.

- (c) Now let's try resolving as many of the remaining errors from above by **adding or removing casting!** For each error that can be resolved with casting, write the modified function call below. Note that you cannot resolve a compile error by creating a runtime error! Also note that not all, or any, of the errors may be resolved.

## 2 Containers

**a) (1 Points).** Suppose that we have the `Container` abstract class below, with the abstract method `pour` and the method `drain`. Implement the method `drain` so that all the liquid is drained from the container, i.e. `amountFilled` is set to 0. Return `true` if any liquid was drained, and `false` otherwise. In other words, return `true` if and only if there is liquid in the container prior to the function being called. You may add a maximum of **5 lines of code**. Note that the staff solution uses 3. You may *only* add code to the `drain` method. (Summer 2021 MT1)

```

1 public abstract class Container {
2     /* Keeps track of the total amount of liquid in the container */
3     public int amountFilled;
4
5     public boolean drain() {
6
7
8
9
10
11     } // You may use at most 5 lines of code, i.e. this bracket should be on line 11 or earlier.
12
13     abstract int pour(int amount);
14 }

```

**b) (1.5 Points).** Finish implementing the `WaterBottle` class so that it is a `Container`. You should *only* add code to the blanks, i.e. **fill in the `pour` method and the class signature**.

As stated in the `Container` class, the `pour` method should pour `amount` into the container and return the amount of the excess liquid, or 0 if there is no excess. For instance, suppose we have a `WaterBottle w` with capacity **10** and `amountFilled` **5**. Then, if we execute `w.pour(7)`, `amountFilled` should be set to **10** and **2** should be returned. Your solution *must* fit within the blanks provided. You may not need all the lines.

```

1 class WaterBottle _____ Container {
2     private static final int DEFAULT_CAPACITY = 16;
3
4     /* The capacity of the container, i.e. the maximum amount of liquid the water bottle can hold */
5     private int capacity;
6
7     WaterBottle() {
8         this(DEFAULT_CAPACITY);
9     }
10    WaterBottle(int capacity) {
11        this.capacity = capacity;
12        this.amountFilled = 0;
13    }

```

```

14
15     @Override
16     public int pour(int amount) {
17         -----;
18         if (-----) {
19             -----;
20             -----;
21             -----;
22         }
23         -----;
24     }
25 }

```

c) (4 Points). Finally, suppose we have the `ContainerList` class, with the `drainFirst` method as implemented below. Unfortunately, the `drainFirst` method *sometimes* errors!

In order to fix it, you may add code to the **ContainerList constructor and the UnknownContainer class!** You may only **use 5 lines of code** in the `ContainerList` constructor and **add 4 lines of code** to the `UnknownContainer` class! If you decide to keep or modify the given line in the `ContainerList` constructor, it counts as one of the 5 lines.

Note that, after making your changes, the `drainFirst` should **never error and retain the functionality in the docstring**. You may **not modify the drainFirst method!** You may use classes from the previous part assuming they are implemented correctly.

Hint: Make sure that, with your fix, the `drainFirst` method won't error, even if the `drainFirst` method is called many times.

```

1  class UnknownContainer ----- {
2      // TODO
3
4
5
6
7
8  } // You may add at most 4 lines of code to the class above
9  // i.e. the closing bracket should be on line 6 or earlier
10
11 class ContainerList {
12     private Container[] containers;
13
14     ContainerList(Container[] conts) {
15         this.containers = conts; // you may delete, modify, or keep this line
16         // YOUR CODE HERE
17
18

```

```
19
20
21
22     } // You may use at most 5 lines of code in the Constructor
23     // i.e. the closing bracket should be on line 18 or earlier
24
25     /* Drains the water from the first nonempty container */
26     void drainFirst() {
27         int index = 0;
28         while (!containers[index].drain()) {
29             index += 1;
30         }
31     }
32 }
```

### 3 Challenge: A Puzzle

Consider the **partially** filled classes for A and B as defined below:

```

1  public class A {
2      public static void main(String[] args) {
3          ___ y = new ___();
4          ___ z = new ___();
5      }
6
7      int fish(A other) {
8          return 1;
9      }
10
11     int fish(B other) {
12         return 2;
13     }
14 }
15
16 class B extends A {
17     @Override
18     int fish(B other) {
19         return 3;
20     }
21 }
```

Note that the only missing pieces of the classes above are static/dynamic types! Fill in the **four** blanks with the appropriate static/dynamic type — A or B — such that the following are true:

1. `y.fish(z)` equals `z.fish(z)`
2. `z.fish(y)` equals `y.fish(y)`
3. `z.fish(z)` does not equal `y.fish(y)`