Quick Review

What is the instruction format for each of the following instructions?

```
add $s0, $s1, $s2                    addi $s0, $s1, 5
beq $zero, $zero, LABEL              slti $s0, $s1, 0
jr $ra                               j LABEL
```

R, I, R, I, I, J

Translate the following instruction into hexadecimal (the `sra funct` field is 3):

```
sra $8, $9, 16
```

[op | rs | rt | rd | shamt | funct] => [0 | 0 | 9 | 8 | 16 | 3] => 0x00094403

Floating Point Number Representation

In general, floating point numbers are represented using a sign and magnitude model. As in integer sign and magnitude, a floating point number's sign is represented by the leading bit (1 for negative numbers, 0 for positive). The magnitude of the float is broken down into an exponent field and a significand or fraction field.

Sign	Magnitude	
Sign	Exponent	Significand

$$\text{float} = (-1)^{\text{sign}} \times (1.\text{Significand})_2 \times 2^{(\text{Exponent} - \text{Bias})}$$

This breakdown is much like standard scientific notation. The exponent determines the value of the bits in the significand (essentially defining an amount to shift the binary point from normalized form). The significand is similar to the mantissa in scientific notation.

Single Precision Floating Point:

31	30 23	22 0
S	EEEEEEEE	FFFFFFFFFFFFFFFFFFFFFFF

(with an exponent bias of 127)

Double Precision Floating Point:

63	62 52	51 0
S	EEEEEEEEEEE	FFFFFFFFFF...FFFFFFFF

(with an exponent bias of 1023)

Exponent	Significand	Meaning
0	0	0
0	Non-zero	Denorm
1~254	Anything	Float
255	0	Infinity
255	Non-zero	NaN

Exponent bias = $2^{(\text{Number of exponents} - 1)} - 1$

Floating Point Exercises

Convert the following decimal numbers into binary (not float).

1.5	0.25	0.8	-16.5
1.1b	0.01b	0.1100b (repeating)	-10000.1b

Give the best hex representation of the following numbers (using single precision floats):

1.0	-7.5	(1.0/3.0)	(186.334/0.0)
0x3f800000	0xc0f00000	0x3eaaaaaa	0x7f800000

What is the value of the following single precision floats?

0x0	0xff94beef	0x1
0.0f	NaN	2^{-149}

Disassembly

The process of translating raw binary instructions into MIPS is called disassembly. Given a simple program, it is possible to translate from a raw binary all the way back to an equivalent C program.

The first step in disassembling a single instruction is to figure out what instruction format it is. This is easy, because all instruction formats conveniently reserve the first 6 bits for the `opcode` field. From the `opcode`, the rest of the bits can be interpreted appropriately.

Disassembly Exercises

Be a processor! Translate the following hex instructions into MIPS:

```
0x8c880000  lw $t0, 0($a0)
0x2108ffff  addi $t0, $t0, -1
0xaca80000  sw $t0, 0($a1)
0x03e00008  jr $ra
```

MAL vs. TAL

MIPS comes in two different flavors: MAL and TAL. MIPS assembly language (MAL) is the more programmer (or lazy compiler) oriented version. It abstracts away the details of immediate field limitations and extends the instruction set. True assembly language (TAL) is the stricter, processor friendly MIPS. There is a one-to-one translation from TAL instructions to binary executables. It is the job of the assembler to translate from MAL to TAL. A single MAL pseudoinstruction might become several TAL instructions.

MAL vs. TAL Exercises

Be an assembler! Translate the following MAL program to TAL:

```
Foo:  bge $s0, $s1, Bar
      swap $s0, $s1
Bar:  beqi $s0, 100, End
      incr $s0
      j Bar
End:  add $s0, $s0, -100
```

```
Foo: slt  $at, $s0, $s1  #There are probably other ways
     beq  $at, $0,  4    #Bar
     add  $at, $0,  $s1
     add  $s1, $s0, $0
     add  $s0, $at, $0
     addi $at, $0,  100
Bar: beq  $s0, $at, 2    #End
     addi $s0, $s0, 1
     j    Bar            #No way to write a number without knowing
End: addi $s0, $s0, -100 #program location in memory
```

Bonus Question:

I have two children, one is a boy and was born on a Tuesday, what's the probability that my other child is a boy?

13/27