


Light Sensor Breadboard Circuit - Cory 140 ¶

Build the ambient light sensor circuit on a breadboard and hook it up to the Launchpad, as you did in Imaging Lab 1. This requires the following parts:

- 1x Breadboard
- 4x Male-to-Male Jumper Wires (Exposed metal connections on both ends)
- 1x Ambient Light Sensor a.k.a. Phototransistor
- 1x 0.1 μ F Capacitor (104)
- 1x 100k Ω Resistor (Brown-Black-Yellow-Gold)
- 1x TI Launchpad MSP430F5529LP
- 1x Micro-USB to USB-A Cable (Long, supplied for this lab)

The schematic that you will build is shown below. Labels in purple indicate connections to the Launchpad. First, we will plug the necessary circuit elements into the breadboard. Follow the instructions below exactly.




Setting up the Breadboard:

- Plug the **long leg of the ambient light sensor** into **Row 16, Column A of the breadboard**, as illustrated in the breadboard diagram above. The short leg should be plugged into the nearest hole in the **red (+) column** of the breadboard.
- Both Setups: Plug one leg of the **100k Ω resistor** into a hole in **Row 6** of the breadboard. Plug its other leg into a nearby hole in the **blue (-) column**.


- Both Setups: In a similar fashion, plug the **0.1 μ F capacitor** into a hole in **Row 6** of the breadboard. The other leg should also be plugged into the **blue (-) column**. *Warning: Make sure that none of the legs are touching each other to prevent shorting!*
- Both Setups: Use a **male-to-male jumper wire** to connect (short) **Row 16, Column E** to **Row 6, Column E**.

Stand Setup


Unlike last week, we care about where the light sensor and other components are placed on the breadboard. **The light sensor should be facing the center of the image being captured (roughly the center of the projected display), and should not be tilted away.** No components, wires, etc. should get in its way. Therefore, everything else is carefully placed to the side. This is evidenced from the photos below:



- Take the plastic stand (with projector) out of the cardboard box at your station. The breadboard should be sitting on top of the stand's raised base (immediately in front of/below the projector). You should **tape the breadboard's side to the stand, as shown in the (Side) photo**. Tape is on the TA desk; do not take the whole dispenser.




- After attaching the breadboard to the stand, place the **Launchpad at the stand's base** and use a **male-to-male jumper wire** to connect **Row 6** (= sensor circuit output) to **P6.0 on the back of the Launchpad (yellow)**. The Launchpad can read analog voltage values from our circuit, convert them into digital values, and then send them over to our computer.
- The Launchpad supplies 3.3V to our circuit. Use a **male-to-male jumper wire** to connect the right-most hole (~Row 1) in the **red (+) column** (3.3V supply) to **3V3 on the back of the Launchpad (green)**.
- Use a **male-to-male jumper wire** to connect the right-most hole in the **blue (-) column** (0V) to **GND on the back of the Launchpad (blue)**.




Again, make sure none of your wires get in the way of the projector or light sensor. If they do, consider taping them down.

Launchpad (MSP430) Setup



- Feed a **long Micro-USB cable** (already connected to your computer on the USB-A end) through the hole in the box closest to the Launchpad's Micro-USB port. Plug it into the Launchpad's Micro-USB port. You can find the cable in the box.
- **Open the AnalogReadSerial program in Energia (File > Open) . This is a different Launchpad code from last week, and can be found in the Imaging Lab 2 folder you downloaded. Upload the code by clicking on the Upload button (white circle with a right-pointing arrow, as shown below):**






- To verify that the program is working, type a **6** into the serial monitor (accessed in **Energia via Tools > Serial Monitor**). You will need to set the **Baud Rate** to **115200** . You should see a reading from the ambient light sensor appear. Take note of the highest and lowest values you can read.

*Note: If you're having any trouble connecting to your Launchpad, double check that the right board is selected via **Tools > Board > MSP-EXP430F5529LP** . Also double check that the right serial port is selected via **Tools > Port > COM#** . In order to upload code to the device, we have to select the serial port that the Launchpad is connected to. Use the **Windows Device Manager** to figure out which COM port is connected to **UART1**.

Projector Setup



Setup the projector with the following steps:

- **Feed the Mini-HDMI cable and projector power cable through the box holes closest to corresponding projector ports (refer back to Launchpad Setup as reference) and connect them to the projector.** The Mini-HDMI cable should already be plugged into the computer. You can likely find it on the computer or behind the monitor. The power adapter should be plugged into one of the outlets at the back of your workstation, behind your keyboard.
- Turn on the projector by holding down the **Power button** (see the previous figure).
- Find the **Focus Adjustment** wheel on the side of the projector to adjust the focus of the projection onto the box. Get it as close as possible.



- Using the left/right arrows on the **Directional Pads**, select **HDMI** on the projector's **main menu**. After a few seconds, you should see the Windows 10 desktop.
- If you see the Windows 10 taskbar at the bottom of the projected screen, take the following precautions:
 1. Hit the **Windows key** and type **Settings**.
 2. Click on the **Personalization** icon.
 3. Click on **Taskbar** on the left side.
 4. Under the **Multiple Displays** section, turn **Show taskbar on all displays** **off**.
- Use the **Back button** on the projector to return to displaying the **main menu**.
- Use the left/right arrows to select the **Settings** option (gears icon).



- Change the **Picture Mode** from Standard to **User**.
- **IMPORTANT:** Use the down arrow to move the cursor down to **Contrast**. Then use the right arrow to adjust the contrast to **100**.
- **IMPORTANT:** Move the cursor down to **Brightness** and use the left arrow to adjust the brightness to **0**.
- To **Confirm the Selection**, hit OK and exit the menu with the **Back button**.
- Again, select **HDMI** on the projector's **main menu** and make sure that you see the Windows 10 desktop on your projector.

MAKE SURE YOU HAVE FOLLOWED ALL THESE STEPS - IF YOU TURN OFF YOUR PROJECTOR THE SETTINGS WILL RESET

